


General Description


Item number	FM-X-X-4095-Z
Date and time	16-10-2020 14:23:26
CCT (Kelvin)	4020 K
Beam angle	6,4°
Luminous flux	8,55 lm
Efficiency	8 lm/watt
Weighted energy	1,0 kWh/1000h
Power factor	1,0
CRI (RA)	94,5
Fidelity index Rf	Rf 92,7
Gammut index Rg	Rg 101,0
Peak	440 cd



Polar diagram



Cartesian diagram



LM-79

Test Report

LM79-FOCUS-MICRO-4000K-CRI95-SPOT

Beam details	1m	2m	3m	4m	5m																			
Lux*	440 lx	110 lx	49 lx	27 lx	18 lx																			
*measured at center of beam																								
Footcandles*	40,8 fcd	10,2 fcd	4,5 fcd	2,6 fcd	1,6 fcd																			
Beam width (meter)	0,1 m	0,2 m	0,3 m	0,4 m	0,6 m																			
Beam width (Feet)	0,4 ft	0,7 ft	1,1 ft	1,5 ft	1,8 ft																			
Beam intensities																								
1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m					
440lx	110lx	49lx	27lx	18lx	12lx	9lx	7lx	5lx	4lx	4lx	3lx	3lx	2lx	2lx	2lx	2lx	1lx	1lx	1lx					
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft					
40,8fcd	10,2fcd	4,5fcd	2,6fcd	1,6fcd	1,1fcd	0,8fcd	0,6fcd	0,5fcd	0,4fcd	0,3fcd	0,3fcd	0,2fcd	0,2fcd	0,2fcd	0,2fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd					
Intensities in 0° c-plane																								
0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°					
440	410	335	239	151	86	47	25	14	8	5	3	2	2	1	1	1	1	1	1					
100%	93%	76%	54%	34%	20%	11%	6%	3%	2%	1%	1%	1%	0%	0%	0%	0%	0%	0%	0%					
Intensities in 90° c-plane																								
0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°					
440	411	337	240	150	84	44	23	12	7	4	3	2	2	1	1	1	1	1	1					
100%	94%	77%	54%	34%	19%	10%	5%	3%	2%	1%	1%	0%	0%	0%	0%	0%	0%	0%	0%					
Intensities in 180° c-plane																								
0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°					
440	409	334	239	151	85	45	24	12	7	4	3	2	2	1	1	1	1	1	1					
100%	93%	76%	54%	34%	19%	10%	5%	3%	2%	1%	1%	0%	0%	0%	0%	0%	0%	0%	0%					
Intensities in 270° c-plane																								
0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°					
440	411	335	239	152	87	47	25	14	8	5	3	2	2	1	1	1	1	1	1					
100%	94%	76%	54%	35%	20%	11%	6%	3%	2%	1%	1%	1%	0%	0%	0%	0%	0%	0%	0%					
Beam angle 50%					Field angle 10%					Cutoff angle 2,5%					Intensity ratio in 120° cone					Intensity ratio in 90° cone				
6,4°					12,1°					16,5°					96,8%					93,9%				



CLS LED BV
 info@cls-led.com
 www.cls-led.com




2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-FOCUS-MICRO-4000K-CRI95-SPOT

Color details



CIE 1931

x: 0,380



Spectra


CIE 1931 ZOOM

4020 K

y: 0,377

Δuv : 0,0004


CRI: 94,5 (R1-R8)



CRI values, R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8
95,8	95,0	92,2	95,5	94,5	91,7	96,7	94,6
R9	R10	R11	R12	R13	R14	R15	
83,9	86,7	94,7	75,0	95,4	95,1	95,3	


CQS: 93,5



CQS values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8
96,6	98,9	86,7	88,0	92,9	93,7	93,3	96,9
Q9	Q10	Q11	Q12	Q13	Q14	Q15	
96,5	93,9	94,4	95,9	97,0	95,3	95,7	

TM30: 92,7



TM30 values, 16 binned values out of total of 99 values

C1	C2	C3	C4	C5	C6	C7	C8
94,7	96,2	92,4	93,5	93,1	95,9	97,1	95,5
C9	C10	C11	C12	C13	C14	C15	
94,0	89,4	85,8	88,4	93,5	94,2	91,2	

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
4020 K	94,5	83,9	92,7	101,0	93,5	0,380	0,377	0,225	0,335	0,0004



CLS LED BV
 info@cls-led.com
 www.cls-led.com

2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-FOCUS-MICRO-4000K-CRI95-SPOT

TM30 details


Rf 92,7

Fidelity index Rf


Rg 101,0

Gamut index Rg


Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	95	-2%	-1%
2	96	-2%	1%
3	92	-1%	4%
4	93	-1%	3%
5	93	0%	2%
6	96	2%	0%
7	97	0%	-1%
8	95	-2%	0%
9	94	-2%	3%
10	89	-3%	6%
11	86	2%	10%
12	88	4%	6%
13	93	5%	0%
14	94	5%	0%
15	91	3%	-5%
16	90	2%	-7%




Hue binH



Color vector graphics




Hue bin



Color distortion graphics



Color Evaluation Sample



CLS LED BV
 info@cls-led.com
 www.cls-led.com

2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

