


#### General Description


Item number	FM-X-X-4095-Z
Date and time	16-10-2020 14:18:21
CCT (Kelvin)	3837 K
Beam angle	91,7°
Luminous flux	80,1 lm
Efficiency	76 lm/watt
Weighted energy	1,1 kWh/1000h
Power factor	1,0
CRI (RA)	93,6
Fidelity index Rf	Rf 93,3
Gammut index Rg	Rg 100,1
Peak	45,5 cd



*Polar diagram*



*Cartesian diagram*



# LM-79

## Test Report

# LM79-FOCUS-MICRO-4000K-CRI95-WIDE

Beam details	1m	2m	3m	4m	5m															
<b>Lux*</b>	45 lx	11 lx	5 lx	3 lx	2 lx															
<b>Footcandles*</b>	4,2 fcd	1,0 fcd	0,5 fcd	0,3 fcd	0,2 fcd															
<b>Beam width (meter)</b>	2,1 m	4,1 m	6,2 m	8,2 m	10,3 m															
<b>Beam width (Feet)</b>	6,8 ft	13,5 ft	20,3 ft	27,1 ft	33,8 ft															
<b>Beam intensities</b>																				
1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m	
45lx	11lx	5lx	3lx	2lx	1lx	1lx	1lx	1lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft	
4,2fcd	1fcd	0,5fcd	0,3fcd	0,2fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	
<b>Intensities in 0° c-plane</b>																				
0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	
44,8	44,3	43,8	43,4	42,4	41,0	39,3	37,4	34,6	26,1	6,2	0,3	0,1	0,1	0,1	0,1	0,1	0,1	0,1	0,0	
100%	99%	98%	97%	95%	92%	88%	83%	77%	58%	14%	1%	0%	0%	0%	0%	0%	0%	0%	0%	
<b>Intensities in 90° c-plane</b>																				
0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	
44,8	44,8	44,7	44,3	43,3	41,8	40,4	38,5	35,6	26,0	5,8	0,3	0,1	0,1	0,1	0,1	0,1	0,1	0,1	0,0	
100%	100%	100%	99%	97%	93%	90%	86%	79%	58%	13%	1%	0%	0%	0%	0%	0%	0%	0%	0%	
<b>Intensities in 180° c-plane</b>																				
0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	
44,8	45,0	45,4	45,4	44,9	44,0	42,5	40,8	38,7	26,9	5,3	0,3	0,1	0,1	0,1	0,1	0,1	0,1	0,0	0,0	
100%	100%	101%	101%	100%	98%	95%	91%	86%	60%	12%	1%	0%	0%	0%	0%	0%	0%	0%	0%	
<b>Intensities in 270° c-plane</b>																				
0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	
44,8	44,8	44,6	44,2	43,5	42,4	41,1	39,2	36,6	26,2	5,3	0,4	0,1	0,1	0,1	0,1	0,1	0,1	0,0	0,0	
100%	100%	100%	99%	97%	95%	92%	88%	82%	58%	12%	1%	0%	0%	0%	0%	0%	0%	0%	0%	
<b>Beam angle 50%</b>		<b>Field angle 10%</b>			<b>Cutoff angle 2,5%</b>			<b>Intensity ratio in 120° cone</b>				<b>Intensity ratio in 90° cone</b>								
91,7°		100,9°			104,9°			99,7%				90,9%								



**CLS LED BV**  
 info@cls-led.com  
 www.cls-led.com




2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website [www.cls-led.com/voorwaarden.pdf](http://www.cls-led.com/voorwaarden.pdf)

# LM-79

## Test Report

### LM79-FOCUS-MICRO-4000K-CRI95-WIDE

#### Color details



CIE 1931

x: 0,391



Spectra

CIE 1931 ZOOM


3837 K

y: 0,392

$\Delta uv$ : 0,0038

**CRI: 93,6 (R1-R8)**


*CRI values, R1-R8 are used to calculate final CRI value*



R1	R2	R3	R4	R5	R6	R7	R8
94,2	93,7	92,1	95,4	92,9	90,8	96,9	93,0
R9	R10	R11	R12	R13	R14	R15	
78,4	84,3	94,8	74,8	93,6	95,1	92,6	

**CQS: 94,3**


*CQS values*



Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8
95,5	99,2	89,2	90,3	93,5	93,6	94,4	97,5
Q9	Q10	Q11	Q12	Q13	Q14	Q15	
97,2	95,3	95,3	96,1	96,7	94,0	94,6	

**TM30: 93,3**

*TM30 values, 16 binned values out of total of 99 values*



C1	C2	C3	C4	C5	C6	C7	C8
94,2	96,1	93,2	94,5	94,1	96,8	97,3	95,6
C9	C10	C11	C12	C13	C14	C15	
94,3	90,3	87,4	89,9	95,6	92,1	92,5	

#### Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	$\Delta uv$
3837 K	93,6	78,4	93,3	100,1	94,3	0,391	0,392	0,226	0,340	0,0038



**CLS LED BV**  
 info@cls-led.com  
 www.cls-led.com

2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website [www.cls-led.com/voorwaarden.pdf](http://www.cls-led.com/voorwaarden.pdf)

# LM-79

## Test Report

# LM79-FOCUS-MICRO-4000K-CRI95-WIDE

### TM30 details


Rf 93,3

Fidelity index Rf


Rg 100,1

Gamut index Rg


Hue Bin	R <sub>f</sub>	Graphic shifts (%)	
		Chroma	Hue
1	94	-3%	-1%
2	96	-2%	0%
3	93	-1%	3%
4	94	-1%	2%
5	94	-1%	2%
6	97	2%	0%
7	97	-1%	-1%
8	96	-2%	0%
9	94	-3%	2%
10	90	-3%	5%
11	87	1%	9%
12	90	3%	5%
13	96	3%	0%
14	92	6%	-3%
15	93	2%	-5%
16	90	1%	-7%




### Hue binH



### Color vector graphics




### Hue bin



### Color distortion graphics



### Color Evaluation Sample



CLS LED BV  
info@cls-led.com  
www.cls-led.com

2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website [www.cls-led.com/voorwaarden.pdf](http://www.cls-led.com/voorwaarden.pdf)

