

LM-79

Test Report


LM79-JADE-HP-4000K-CRI90-SPOT

General Discription


Item number	
Date and time	1-3-2021 14:18:09
CCT (Kelvin)	3997 K
Beam angle	18,8°
Luminous flux	3848 lm
Efficiency	94 lm/watt
Weighted energy	41,1 kWh/1000h
Power factor	0,99
CRI (RA)	92,1
Fidelity index Rf	Rf 90,0
Gammut index Rg	Rg 97,7
Peak	17856 cd



Polar diagram



Cartesian diagram




CLS LED BV
info@cls-led.com
www.cls-led.com

2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-JADE-HP-4000K-CRI90-SPOT

Beam details					1m		2m		3m		4m		5m						
Lux*					17856 lx		4464 lx		1984 lx		1116 lx		714 lx						
18,8° 																			
*measured at center of beam																			
Footcandles*					1658,9 fcd		414,7 fcd		184,3 fcd		103,7 fcd		66,4 fcd						
Beam width (meter)					0,3 m		0,7 m		1 m		1,3 m		1,7 m						
Beam width (Feet)					1,1 ft		2,2 ft		3,3 ft		4,3 ft		5,4 ft						
Beam intensities																			
1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
17856lx	4464lx	1984lx	1116lx	714lx	496lx	364lx	279lx	220lx	179lx	148lx	124lx	106lx	91lx	79lx	70lx	62lx	55lx	49lx	45lx
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
1658,9fcd	414,7fcd	184,3fcd	103,7fcd	66,4fcd	46,1fcd	33,9fcd	25,9fcd	20,5fcd	16,6fcd	13,7fcd	11,5fcd	9,8fcd	8,5fcd	7,4fcd	6,5fcd	5,7fcd	5,1fcd	4,6fcd	4,1fcd
Intensities in 0° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
17,9K	17,3K	15,7K	13,4K	10,8K	8,2K	6,0K	4,4K	3,2K	2,5K	2,1K	1,8K	1,6K	1,5K	1,4K	1,3K	1,2K	1,1K	0,9K	0,6K
100%	97%	88%	75%	60%	46%	34%	24%	18%	14%	12%	10%	9%	8%	8%	7%	7%	6%	5%	4%
Intensities in 90° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
17,9K	17,3K	15,7K	13,4K	10,8K	8,2K	6,0K	4,4K	3,2K	2,5K	2,1K	1,8K	1,6K	1,5K	1,4K	1,3K	1,2K	1,1K	0,9K	0,6K
100%	97%	88%	75%	60%	46%	34%	24%	18%	14%	12%	10%	9%	8%	8%	7%	7%	6%	5%	4%
Intensities in 180° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
17,9K	17,3K	15,7K	13,4K	10,8K	8,2K	6,0K	4,4K	3,2K	2,5K	2,1K	1,8K	1,6K	1,5K	1,4K	1,3K	1,2K	1,1K	0,9K	0,6K
100%	97%	88%	75%	60%	46%	34%	24%	18%	14%	12%	10%	9%	8%	8%	7%	7%	6%	5%	4%
Intensities in 270° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
17,9K	17,3K	15,7K	13,4K	10,8K	8,2K	6,0K	4,4K	3,2K	2,5K	2,1K	1,8K	1,6K	1,5K	1,4K	1,3K	1,2K	1,1K	0,9K	0,6K
100%	97%	88%	75%	60%	46%	34%	24%	18%	14%	12%	10%	9%	8%	8%	7%	7%	6%	5%	4%
Beam angle 50%				Field angle 10%				Cutoff angle 2,5%				Intensity ratio in 120° cone				Intensity ratio in 90° cone			
18,8°				43,9°				79,8°				98,3%				95,7%			



CLS LED BV
info@cls-led.com
www.cls-led.com




2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-JADE-HP-4000K-CRI90-SPOT

Color details



CIE 1931

x: 0,381

3997 K


y: 0,377

Spectra

CIE 1931 ZOOM

Δuv : -0,0001


CRI: 92,1 (R1-R8)



CRI values, R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8
92,3	95,7	97,0	91,6	91,3	92,7	93,0	83,5
R9	R10	R11	R12	R13	R14	R15	
58,9	88,6	91,7	71,7	93,5	98,2	89,1	


CQS: 90,8



CQS values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8
89,8	98,2	86,6	84,6	88,8	91,1	93,0	94,4
Q9	Q10	Q11	Q12	Q13	Q14	Q15	
98,8	94,7	93,1	92,9	92,8	87,7	88,7	

TM30: 90,0



TM30 values, 16 binned values out of total of 99 values

C1	C2	C3	C4	C5	C6	C7	C8
89,3	92,3	90,3	92,6	92,6	96,3	93,9	92,5
C9	C10	C11	C12	C13	C14	C15	
89,1	84,9	84,5	89,6	90,2	93,0	86,0	

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3997 K	92,1	58,9	90,0	97,7	90,8	0,381	0,377	0,225	0,334	-0,0001



CLS LED BV
info@cls-led.com
www.cls-led.com

2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-JADE-HP-4000K-CRI90-SPOT

TM30 details


Rf 90,0

Fidelity index Rf


Rg 97,7

Gamut index Rg


Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	89	-6%	0%
2	92	-3%	2%
3	90	-2%	4%
4	93	-2%	2%
5	93	-3%	1%
6	96	-1%	0%
7	94	-4%	0%
8	93	-4%	3%
9	89	-3%	7%
10	85	-2%	9%
11	85	4%	10%
12	90	4%	3%
13	90	4%	-5%
14	93	3%	-4%
15	86	0%	-9%
16	86	-2%	-8%




Hue binH



Color vector graphics




Hue bin



Color distortion graphics



Color Evaluation Sample



CLS LED BV
info@cls-led.com
www.cls-led.com

2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-JADE-HP-4000K-CRI90-SPOT

Glare Evaluation According to UGR

p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	22,5	23,0	22,6	23,2	23,4	22,5	23,0	22,6	23,2	23,4
	3H	22,4	23,1	22,8	23,3	23,5	22,4	23,1	22,8	23,3	23,5
	4H	22,5	23,2	22,9	23,4	23,6	22,5	23,2	22,9	23,4	23,6
	6H	22,6	23,2	22,9	23,5	23,8	22,6	23,2	22,9	23,5	23,8
	8H	22,6	23,1	22,9	23,5	23,8	22,6	23,1	22,9	23,5	23,8
	12H	22,6	23,1	22,9	23,4	23,8	22,6	23,1	22,9	23,4	23,8
4H	2H	22,2	22,9	22,6	23,1	23,3	22,2	22,9	22,6	23,1	23,3
	3H	22,5	23,0	22,8	23,4	23,8	22,5	23,0	22,8	23,4	23,8
	4H	22,6	23,0	23,0	23,5	24,0	22,6	23,0	23,0	23,5	24,0
	6H	22,7	23,2	23,2	23,5	23,9	22,7	23,2	23,2	23,5	23,9
	8H	22,7	23,2	23,2	23,5	23,9	22,7	23,2	23,2	23,5	23,9
	12H	22,6	23,0	23,1	23,4	23,9	22,6	23,0	23,1	23,4	23,9
8H	4H	22,6	23,0	23,1	23,4	23,7	22,6	23,0	23,1	23,4	23,7
	6H	22,7	23,1	23,2	23,5	24,0	22,7	23,1	23,2	23,5	24,0
	8H	22,8	23,1	23,3	23,6	24,2	22,8	23,1	23,3	23,6	24,2
	12H	22,8	23,0	23,4	23,5	24,1	22,8	23,0	23,4	23,5	24,1
12H	4H	22,5	22,9	23,0	23,3	23,7	22,5	22,9	23,0	23,3	23,7
	6H	22,8	23,0	23,3	23,5	24,2	22,8	23,0	23,3	23,5	24,2
	8H	22,8	23,0	23,4	23,5	24,1	22,8	23,0	23,4	23,5	24,1
Variation of the observer position for the luminaire distance S											
S = 1.0H		3,8 / -3,2					3,8 / -3,2				
S = 1.5H		6,2 / -3,5					6,2 / -3,5				
S = 2.0H		8,1 / -3,9					8,1 / -3,9				
Standard table		n/a					n/a				
Correction summand		n/a					n/a				
Corrected glare indices referring to 3848lm total luminous flux											



CLS LED BV
 info@cls-led.com
 www.cls-led.com

2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf