

LM-79

Test Report

LM79-JADE-S-3000K-CRI80-MEDIUM

General Discription

Item number	J-SX-X-3-1-27-80-2
Date and time	25-11-2016 13:41:37
CCT (Kelvin)	3097 K
Beam angle	36,9°
Luminous flux	2975 lm
Efficiency	105 lm/watt
Weighted energy	28,4 kWh/1000h
Power factor	0,99
CRI (RA)	81,5
Fidelity index Rf	Rf 82,8
Gammut index Rg	Rg 95,8

NEW



CLS LED BV
info@cls-led.com
www.cls-led.com

2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-JADE-S-3000K-CRI80-MEDIUM

Beam details	1m	2m	3m	4m	5m
Lux*	5570 lx	1393 lx	619 lx	348 lx	223 lx

*measured at center of beam

Footcandles*	517,5 fcd	129,4 fcd	57,5 fcd	32,3 fcd	20,7 fcd
Beam width (meter)	0,7 m	1,3 m	2 m	2,7 m	3,3 m
Beam width (Feet)	2,2 ft	4,4 ft	6,6 ft	8,8 ft	11 ft

Beam intensities																			
1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
5570lx	1393lx	619lx	348lx	223lx	155lx	114lx	87lx	69lx	56lx	46lx	39lx	33lx	28lx	25lx	22lx	19lx	17lx	15lx	14lx
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
517,5fcd	129,4fcd	57,5fcd	32,3fcd	20,7fcd	14,4fcd	10,6fcd	8,1fcd	6,4fcd	5,2fcd	4,3fcd	3,6fcd	3,1fcd	2,6fcd	2,3fcd	2fcd	1,8fcd	1,6fcd	1,4fcd	1,3fcd

Intensities in 0° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
5570	5570	5395	5182	4897	4531	4156	3721	3286	2875	2471	2125	1848	1586	1420	1255	1090	923	744	549
100%	100%	97%	93%	88%	81%	75%	67%	59%	52%	44%	38%	33%	28%	25%	23%	20%	17%	13%	10%

Intensities in 90° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
5570	5549	5389	5165	4877	4516	4138	3721	3298	2882	2480	2127	1846	1596	1415	1250	1089	923	741	546
100%	100%	97%	93%	88%	81%	74%	67%	59%	52%	45%	38%	33%	29%	25%	22%	20%	17%	13%	10%

Intensities in 180° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
5570	5570	5395	5182	4897	4531	4156	3721	3286	2875	2471	2125	1848	1586	1420	1255	1090	923	744	549
100%	100%	97%	93%	88%	81%	75%	67%	59%	52%	44%	38%	33%	28%	25%	23%	20%	17%	13%	10%

Intensities in 270° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
5570	5549	5389	5165	4877	4516	4138	3721	3298	2882	2480	2127	1846	1596	1415	1250	1089	923	741	546
100%	100%	97%	93%	88%	81%	74%	67%	59%	52%	45%	38%	33%	29%	25%	22%	20%	17%	13%	10%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
36,9°	75,8°	{C_ANG}°	97,7%	95,3%



CLS LED BV
 info@cls-led.com
 www.cls-led.com




2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-JADE-S-3000K-CRI80-MEDIUM

Color details



CIE 1931

x: 0,435

3097 K


y: 0,412

Spectra

CIE 1931 ZOOM

Δuv : 0,0035


CRI: 81,5 (R1-R8)



CRI values, R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8
79,1	87,7	96,1	80,8	78,6	84,4	85,2	60,3
R9	R10	R11	R12	R13	R14	R15	
4,8	71,9	79,6	63,9	80,8	97,6	70,9	


CQS: 78,0



CQS values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8
70,1	94,9	77,8	68,7	71,8	76,5	80,4	86,5
Q9	Q10	Q11	Q12	Q13	Q14	Q15	
89,1	89,2	86,0	84,9	83,6	68,5	68,7	

TM30: 82,8



TM30 values, 16 binned values out of total of 99 values

C1	C2	C3	C4	C5	C6	C7	C8
77,4	79,0	75,1	86,1	91,6	92,3	84,9	91,8
C9	C10	C11	C12	C13	C14	C15	
87,5	78,7	77,1	85,6	88,0	79,7	77,1	

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3097 K	81,5	4,8	82,8	95,8	78,0	0,435	0,412	0,246	0,350	0,0035



CLS LED BV
info@cls-led.com
www.cls-led.com

2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-JADE-S-3000K-CRI80-MEDIUM

TM30 details


Rf 82,8

Fidelity index Rf


Rg 95,8

Gamut index Rg


Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	77	-11%	-1%
2	79	-9%	6%
3	75	-4%	11%
4	86	1%	8%
5	92	2%	5%
6	92	3%	-2%
7	85	-3%	-8%
8	92	-4%	-2%
9	87	-7%	2%
10	79	-6%	9%
11	77	-2%	14%
12	86	6%	4%
13	88	5%	-5%
14	80	6%	-13%
15	77	-2%	-13%
16	76	-7%	-15%




Hue binH



Color vector graphics




Hue bin



Color distortion graphics



Color Evaluation Sample



CLS LED BV
info@cls-led.com
www.cls-led.com

2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

Glare Evaluation According to UGR

p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	22,1	22,8	22,4	23,0	23,2	22,1	22,8	22,4	23,0	23,2
	3H	22,2	22,8	22,5	23,1	23,3	22,2	22,8	22,5	23,0	23,3
	4H	22,2	22,8	22,5	23,1	23,3	22,2	22,8	22,5	23,1	23,3
	6H	22,2	22,8	22,6	23,1	23,4	22,2	22,8	22,6	23,1	23,4
	8H	22,2	22,8	22,6	23,1	23,4	22,2	22,7	22,6	23,0	23,4
	12H	22,2	22,7	22,6	23,0	23,4	22,2	22,7	22,6	23,0	23,3
4H	2H	22,0	22,6	22,3	22,9	23,1	22,0	22,6	22,3	22,8	23,1
	3H	22,1	22,6	22,5	22,9	23,3	22,1	22,6	22,5	22,9	23,3
	4H	22,2	22,7	22,6	23,0	23,4	22,2	22,7	22,6	23,0	23,4
	6H	22,3	22,7	22,7	23,1	23,4	22,3	22,7	22,7	23,0	23,4
	8H	22,3	22,7	22,8	23,0	23,5	22,3	22,6	22,8	23,0	23,5
	12H	22,3	22,6	22,8	23,0	23,5	22,3	22,6	22,8	23,0	23,4
8H	4H	22,2	22,5	22,7	22,9	23,4	22,2	22,5	22,6	22,9	23,3
	6H	22,3	22,6	22,8	23,0	23,5	22,3	22,6	22,8	23,0	23,5
	8H	22,4	22,6	22,9	23,0	23,5	22,4	22,6	22,8	23,0	23,5
	12H	22,4	22,6	22,9	23,0	23,5	22,4	22,5	22,9	23,0	23,5
12H	4H	22,2	22,5	22,6	22,9	23,3	22,2	22,5	22,6	22,9	23,3
	6H	22,3	22,5	22,8	23,0	23,5	22,3	22,5	22,8	23,0	23,5
	8H	22,4	22,5	22,9	23,0	23,5	22,4	22,5	22,9	23,0	23,5
Variation of the observer position for the luminaire distance S											
S = 1,0H		+4,0 / -3,9					+4,0 / -3,9				
S = 1,5H		+6,6 / -4,3					+6,6 / -4,3				
S = 2,0H		+8,5 / -4,6					+8,5 / -4,6				
Standard table		BK01					BK01				
Correction summand		4,2					4,2				
Corrected glare indices referring to 2975lm total luminous flux											

