

LM-79

Test Report

LM79-REVO-3000K-CRI80-DEG30

General Discription

Item number	R-X-X-X-03-3
Date and time	22-4-2016 10:53:56
CCT (Kelvin)	2995 K
Beam angle	29,3°
Luminous flux	1417 lm
Efficiency	74 lm/watt
Weighted energy	19,2 kWh/1000h
Power factor	0,94
CRI (RA)	83,3
Fidelity index Rf	Rf 84,4
Gammut index Rg	Rg 96,6



CLS LED BV
info@cls-led.com
www.cls-led.com

2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-REVO-3000K-CRI80-DEG30

Beam details		1m	2m	3m	4m	5m
Lux*		4634 lx	1159 lx	515 lx	290 lx	185 lx

29,3°

*measured at center of beam

Footcandles*		430,5 fcd	107,6 fcd	47,8 fcd	26,9 fcd	17,2 fcd
Beam width (meter)		0,5 m	1 m	1,6 m	2,1 m	2,6 m
Beam width (Feet)		1,7 ft	3,4 ft	5,1 ft	6,9 ft	8,6 ft

Beam intensities																			
1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
4634lx	1159lx	515lx	290lx	185lx	129lx	95lx	72lx	57lx	46lx	38lx	32lx	27lx	24lx	21lx	18lx	16lx	14lx	13lx	12lx
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
430,5fcd	107,6fcd	47,8fcd	26,9fcd	17,2fcd	12fcd	8,8fcd	6,7fcd	5,3fcd	4,3fcd	3,6fcd	3fcd	2,5fcd	2,2fcd	1,9fcd	1,7fcd	1,5fcd	1,3fcd	1,2fcd	1,1fcd

Intensities in 0° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
4634	4596	4396	4125	3731	3306	2849	2411	1976	1579	1209	912	658	478	331	238	167	122	89	67
100%	99%	95%	89%	81%	71%	61%	52%	43%	34%	26%	20%	14%	10%	7%	5%	4%	3%	2%	1%

Intensities in 90° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
4634	4578	4393	4108	3730	3317	2893	2484	2088	1708	1347	1026	753	544	385	275	196	142	104	79
100%	99%	95%	89%	80%	72%	62%	54%	45%	37%	29%	22%	16%	12%	8%	6%	4%	3%	2%	2%

Intensities in 180° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
4634	4596	4396	4125	3731	3306	2849	2411	1976	1579	1209	912	658	478	331	238	167	122	89	67
100%	99%	95%	89%	81%	71%	61%	52%	43%	34%	26%	20%	14%	10%	7%	5%	4%	3%	2%	1%

Intensities in 270° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
4634	4578	4393	4108	3730	3317	2893	2484	2088	1708	1347	1026	753	544	385	275	196	142	104	79
100%	99%	95%	89%	80%	72%	62%	54%	45%	37%	29%	22%	16%	12%	8%	6%	4%	3%	2%	2%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
29,3°	53,1°	69,7°	98,4%	96,5%



CLS LED BV
 info@cls-led.com
 www.cls-led.com




2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-REVO-3000K-CRI80-DEG30

Color details



CIE 1931

x: 0,440

2995 K


y: 0,408

Spectra

CIE 1931 ZOOM

 $\Delta uv: 0,0014$


CRI: 83,3 (R1-R8)



CRI values, R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8
80,9	90,0	97,5	82,1	81,3	88,1	84,8	62,2
R9	R10	R11	R12	R13	R14	R15	
13,0	77,8	81,2	76,1	82,7	98,8	73,5	


CQS: 82,9



CQS values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8
74,9	95,1	84,2	79,7	82,5	84,0	84,6	89,3
Q9	Q10	Q11	Q12	Q13	Q14	Q15	
95,1	92,8	89,4	87,1	85,4	72,4	73,1	

TM30: 84,4



TM30 values, 16 binned values out of total of 99 values

C1	C2	C3	C4	C5	C6	C7	C8
79,1	80,0	76,3	85,3	91,8	91,7	84,2	92,1
C9	C10	C11	C12	C13	C14	C15	
88,5	86,1	83,7	85,6	88,0	81,3	78,0	

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2995 K	83,3	13,0	84,4	96,6	82,9	0,440	0,408	0,250	0,349	0,0014



CLS LED BV
info@cls-led.com
www.cls-led.com

2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-REVO-3000K-CRI80-DEG30

TM30 details


Rf 84,4

Fidelity index Rf


Rg 96,6

Gamut index Rg


Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	79	-11%	-1%
2	80	-8%	7%
3	76	-3%	11%
4	85	3%	8%
5	92	4%	4%
6	92	4%	-3%
7	84	-1%	-9%
8	92	-3%	-3%
9	89	-6%	0%
10	86	-6%	5%
11	84	-2%	10%
12	86	4%	3%
13	88	5%	-6%
14	81	4%	-13%
15	78	-2%	-13%
16	80	-8%	-12%




Hue binH



Color vector graphics




Hue bin



Color distortion graphics



Color Evaluation Sample



CLS LED BV
info@cls-led.com
www.cls-led.com

2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

Glare Evaluation According to UGR

p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	11,5	12,1	11,7	12,3	12,5	11,8	12,5	12,1	12,7	12,9
	3H	11,9	12,5	12,2	12,7	13,0	12,2	12,8	12,4	13,0	13,3
	4H	12,0	12,6	12,3	12,8	13,1	12,2	12,8	12,6	13,1	13,3
	6H	12,0	12,6	12,4	12,8	13,1	12,3	12,8	12,6	13,1	13,4
	8H	12,0	12,5	12,4	12,8	13,1	12,3	12,8	12,6	13,1	13,4
	12H	12,0	12,5	12,3	12,8	13,1	12,3	12,7	12,6	13,0	13,4
4H	2H	11,6	12,2	12,0	12,5	12,7	11,9	12,5	12,3	12,8	13,1
	3H	12,2	12,6	12,5	13,0	13,3	12,4	12,9	12,8	13,2	13,5
	4H	12,4	12,8	12,7	13,1	13,5	12,6	13,0	12,9	13,3	13,7
	6H	12,4	12,8	12,8	13,1	13,5	12,6	13,0	13,0	13,4	13,7
	8H	12,4	12,7	12,8	13,1	13,5	12,6	12,9	13,1	13,3	13,7
	12H	12,4	12,7	12,8	13,1	13,5	12,6	12,9	13,1	13,3	13,7
8H	4H	12,4	12,7	12,8	13,1	13,5	12,6	12,9	13,0	13,3	13,7
	6H	12,5	12,7	12,9	13,1	13,6	12,7	12,9	13,1	13,3	13,8
	8H	12,5	12,7	12,9	13,1	13,6	12,7	12,9	13,2	13,3	13,8
	12H	12,5	12,6	13,0	13,1	13,6	12,7	12,8	13,2	13,3	13,8
12H	4H	12,3	12,6	12,8	13,0	13,5	12,5	12,8	13,0	13,2	13,6
	6H	12,4	12,6	12,9	13,1	13,5	12,7	12,8	13,1	13,3	13,8
	8H	12,4	12,6	12,9	13,1	13,6	12,7	12,8	13,2	13,3	13,8
Variation of the observer position for the luminaire distance S											
S = 1,0H		+2,5 / -1,5					+2,9 / -1,7				
S = 1,5H		+4,6 / -1,9					+5,1 / -2,4				
S = 2,0H		+6,3 / -2,9					+6,8 / -3,1				
Standard table		BK02					BK02				
Correction summand		-5,5					-5,2				
Corrected glare indices referring to 1417lm total luminous flux											

