

LM-79

Test Report

LM79-REVO-AMBER-DEG12

General Discription

Item number	R-X-X-X-31-1
Date and time	27-6-2016 11:30:10
CCT (Kelvin)	1832 K
Beam angle	13,6°
Luminous flux	929 lm
Efficiency	52 lm/watt
Weighted energy	17,8 kWh/1000h
Power factor	0,95
CRI (RA)	37,6
Fidelity index Rf	Rf 43,3
Gammut index Rg	Rg 50,9



CLS LED BV
info@cls-led.com
www.cls-led.com

2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-REVO-AMBER-DEG12

Beam details		1m	2m	3m	4m	5m
Lux*		11454 lx	2864 lx	1273 lx	716 lx	458 lx

13,6°

*measured at center of beam

Footcandles*		1064,2 fcd	266,0 fcd	118,2 fcd	66,5 fcd	42,6 fcd
Beam width (meter)		0,2 m	0,5 m	0,7 m	1 m	1,2 m
Beam width (Feet)		0,8 ft	1,6 ft	2,3 ft	3,1 ft	3,9 ft

Beam intensities																			
1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
11454lx	2864lx	1273lx	716lx	458lx	318lx	234lx	179lx	141lx	115lx	95lx	80lx	68lx	58lx	51lx	45lx	40lx	35lx	32lx	29lx
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
1064,2fcd	266fcd	118,2fcd	66,5fcd	42,6fcd	29,6fcd	21,7fcd	16,6fcd	13,1fcd	10,6fcd	8,8fcd	7,4fcd	6,3fcd	5,4fcd	4,7fcd	4,2fcd	3,7fcd	3,3fcd	2,9fcd	2,7fcd

Intensities in 0° c-plane																			
0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
11,5K	11,3K	10,8K	10,0K	9,0K	7,8K	6,6K	5,3K	4,2K	3,2K	2,4K	1,8K	1,3K	1,0K	0,7K	0,5K	0,4K	0,3K	0,3K	0,2K
100%	99%	95%	88%	79%	68%	57%	46%	36%	28%	21%	15%	11%	8%	6%	5%	4%	3%	2%	2%

Intensities in 90° c-plane																			
0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
11,5K	11,1K	10,4K	9,4K	8,3K	7,0K	5,8K	4,6K	3,5K	2,7K	2,0K	1,4K	1,0K	0,8K	0,6K	0,4K	0,3K	0,3K	0,2K	0,2K
100%	97%	91%	82%	72%	61%	50%	40%	31%	23%	17%	12%	9%	7%	5%	4%	3%	2%	2%	2%

Intensities in 180° c-plane																			
0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
11,5K	11,3K	10,8K	10,0K	9,1K	8,0K	6,8K	5,6K	4,6K	3,7K	2,9K	2,3K	1,9K	1,5K	1,2K	1,0K	0,8K	0,6K	0,5K	0,4K
100%	98%	94%	88%	79%	69%	59%	49%	40%	32%	26%	20%	16%	13%	11%	9%	7%	6%	4%	4%

Intensities in 270° c-plane																			
0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
11,5K	11,5K	11,1K	10,6K	9,7K	8,7K	7,6K	6,5K	5,4K	4,4K	3,6K	2,9K	2,3K	1,9K	1,6K	1,3K	1,0K	0,8K	0,7K	0,6K
100%	100%	97%	92%	85%	76%	66%	56%	47%	38%	31%	25%	20%	17%	14%	11%	9%	7%	6%	5%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
13,6°	26,9°	38,4°	98,9%	97,6%



CLS LED BV
info@cls-led.com
www.cls-led.com




2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-REVO-AMBER-DEG12

Color details



CIE 1931

x: 0,562

1832 K


y: 0,429

Spectra

CIE 1931 ZOOM

Δuv : 0,0065


CRI: 37,6 (R1-R8)



CRI values, R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8
27,8	64,8	84,6	10,8	18,0	45,3	57,0	-7,4
R9	R10	R11	R12	R13	R14	R15	
-113,4	31,2	-20,5	-5,1	30,8	90,6	23,8	


CQS: 0,0



CQS values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8
0,0	55,5	44,4	3,9	0,3	0,0	0,0	0,0
Q9	Q10	Q11	Q12	Q13	Q14	Q15	
0,0	0,0	0,0	0,0	0,0	0,0	0,0	

TM30: 43,3



TM30 values, 16 binned values out of total of 99 values

C1	C2	C3	C4	C5	C6	C7	C8
30,5	29,1	14,8	54,1	69,1	63,8	53,0	35,8
C9	C10	C11	C12	C13	C14	C15	
29,4	23,0	25,2	36,5	70,8	68,8	67,6	

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
1832 K	37,6	-113,4	43,3	50,9	0,0	0,562	0,429	0,320	0,367	0,0065



CLS LED BV
info@cls-led.com
www.cls-led.com

2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-REVO-AMBER-DEG12

TM30 details


Rf 43,3

Fidelity index Rf


Rg 50,9

Gamut index Rg


Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	30	-31%	-8%
2	29	-38%	-2%
3	15	-41%	6%
4	54	-33%	10%
5	69	-29%	5%
6	64	-25%	1%
7	53	-27%	-8%
8	36	-42%	-10%
9	29	-34%	-5%
10	23	-40%	14%
11	25	-32%	27%
12	36	-21%	30%
13	71	-18%	7%
14	69	-18%	-14%
15	68	-13%	-9%
16	49	-27%	-14%




Hue binH




Color vector graphics




Hue bin



Color distortion graphics



Color Evaluation Sample



CLS LED BV
info@cls-led.com
www.cls-led.com

2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

Glare Evaluation According to UGR

p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	20,2	20,9	20,5	21,1	21,3	20,2	20,9	20,4	21,1	21,3
	3H	20,8	21,4	21,1	21,6	21,9	20,6	21,2	20,9	21,5	21,7
	4H	20,9	21,4	21,2	21,7	22,0	20,7	21,3	21,0	21,5	21,8
	6H	21,0	21,5	21,3	21,8	22,1	20,8	21,3	21,1	21,6	21,9
	8H	21,0	21,5	21,4	21,8	22,1	20,8	21,3	21,1	21,6	21,9
	12H	21,1	21,6	21,5	21,9	22,2	20,8	21,2	21,1	21,6	21,9
4H	2H	20,6	21,1	20,9	21,4	21,7	20,5	21,0	20,8	21,3	21,6
	3H	21,3	21,7	21,6	22,0	22,4	21,0	21,5	21,4	21,8	22,1
	4H	21,4	21,8	21,8	22,2	22,5	21,2	21,6	21,5	21,9	22,3
	6H	21,6	21,9	22,0	22,3	22,6	21,3	21,6	21,7	22,0	22,4
	8H	21,7	22,0	22,1	22,3	22,7	21,3	21,6	21,7	22,0	22,4
	12H	21,8	22,1	22,3	22,5	22,9	21,3	21,6	21,8	22,0	22,4
8H	4H	21,5	21,8	21,9	22,2	22,6	21,2	21,5	21,6	21,9	22,3
	6H	21,7	21,9	22,2	22,3	22,8	21,4	21,6	21,8	22,0	22,5
	8H	21,9	22,0	22,3	22,5	23,0	21,4	21,6	21,9	22,1	22,6
	12H	22,1	22,3	22,6	22,7	23,3	21,5	21,6	22,0	22,1	22,6
12H	4H	21,5	21,7	21,9	22,1	22,6	21,2	21,4	21,6	21,8	22,3
	6H	21,7	21,9	22,2	22,3	22,8	21,4	21,6	21,9	22,0	22,5
	8H	21,9	22,0	22,4	22,5	23,0	21,5	21,6	21,9	22,1	22,6
Variation of the observer position for the luminaire distance S											
S = 1,0H		+1,0 / -1,0					+1,1 / -0,9				
S = 1,5H		+2,4 / -1,6					+2,4 / -1,7				
S = 2,0H		+3,7 / -2,1					+3,9 / -2,6				
Standard table		BK03					BK02				
Correction summand		4,1					3,4				
Corrected glare indices referring to 929lm total luminous flux											

