

LM-79

Test Report


LM79-REVO-COMPACT-2200K-CRI80-DEG30

General Discription


Item number	RC-X-X-08-3
Date and time	29-10-2021 11:44:51
CCT (Kelvin)	2191 K
Beam angle	29,5°
Luminous flux	551 lm
Efficiency	55 lm/watt
Weighted energy	10,0 kWh/1000h
Power factor	0,95
CRI (RA)	85,7
Fidelity index Rf	Rf 88,2
Gammut index Rg	Rg 96,0
Peak	1776 cd



Polar diagram



Cartesian diagram



CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-REVO-COMPACT-2200K-CRI80-DEG30

Beam details	1m	2m	3m	4m	5m														
Lux*	1776 lx	444 lx	197 lx	111 lx	71 lx														
*measured at center of beam																			
Footcandles*	165,0 fcd	41,3 fcd	18,3 fcd	10,3 fcd	6,6 fcd														
Beam width (meter)	0,5 m	1,1 m	1,6 m	2,1 m	2,6 m														
Beam width (Feet)	1,7 ft	3,5 ft	5,2 ft	6,9 ft	8,6 ft														
Beam intensities																			
1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
1776lx	444lx	197lx	111lx	71lx	49lx	36lx	28lx	22lx	18lx	15lx	12lx	11lx	9lx	8lx	7lx	6lx	5lx	5lx	4lx
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
165fcd	41,3fcd	18,3fcd	10,3fcd	6,6fcd	4,6fcd	3,4fcd	2,6fcd	2fcd	1,7fcd	1,4fcd	1,1fcd	1fcd	0,8fcd	0,7fcd	0,6fcd	0,6fcd	0,5fcd	0,5fcd	0,4fcd
Intensities in 0° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1776	1770	1730	1622	1462	1284	1110	946	795	649	507	379	273	193	136	96	69	50	38	29
100%	100%	97%	91%	82%	72%	62%	53%	45%	37%	29%	21%	15%	11%	8%	5%	4%	3%	2%	2%
Intensities in 90° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1776	1770	1730	1622	1462	1284	1110	946	795	649	507	379	273	193	136	96	69	50	38	29
100%	100%	97%	91%	82%	72%	62%	53%	45%	37%	29%	21%	15%	11%	8%	5%	4%	3%	2%	2%
Intensities in 180° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1776	1770	1730	1622	1462	1284	1110	946	795	649	507	379	273	193	136	96	69	50	38	29
100%	100%	97%	91%	82%	72%	62%	53%	45%	37%	29%	21%	15%	11%	8%	5%	4%	3%	2%	2%
Intensities in 270° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1776	1770	1730	1622	1462	1284	1110	946	795	649	507	379	273	193	136	96	69	50	38	29
100%	100%	97%	91%	82%	72%	62%	53%	45%	37%	29%	21%	15%	11%	8%	5%	4%	3%	2%	2%
Beam angle 50%		Field angle 10%				Cutoff angle 2,5%				Intensity ratio in 120° cone				Intensity ratio in 90° cone					
29,5°		52,9°				69,7°				98,9%				96,7%					



CLS LED BV
 info@cls-led.com
 www.cls-led.com




2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-REVO-COMPACT-2200K-CRI80-DEG30

Color details



CIE 1931

x: 0,511



Spectra

CIE 1931 ZOOM


2191 K

y: 0,422

Δuv : 0,0020

CRI: 85,7 (R1-R8)


CRI values, R1-R8 are used to calculate final CRI value



R1	R2	R3	R4	R5	R6	R7	R8
84,3	93,0	97,1	85,3	84,6	94,8	83,8	62,7
R9	R10	R11	R12	R13	R14	R15	
23,6	85,2	87,3	86,0	86,2	99,4	75,7	

CQS: 79,9


CQS values



Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8
72,8	87,0	86,8	83,7	81,9	81,5	82,9	85,9
Q9	Q10	Q11	Q12	Q13	Q14	Q15	
87,6	84,0	80,3	81,2	80,9	69,7	71,4	

TM30: 88,2

TM30 values, 16 binned values out of total of 99 values



C1	C2	C3	C4	C5	C6	C7	C8
82,7	84,9	83,5	91,0	94,1	93,7	89,9	96,5
C9	C10	C11	C12	C13	C14	C15	
91,5	91,3	91,4	90,1	89,2	70,7	87,7	

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2191 K	85,7	23,6	88,2	96,0	79,9	0,511	0,422	0,291	0,359	0,0020



CLS LED BV
 info@cls-led.com
 www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-REVO-COMPACT-2200K-CRI80-DEG30

TM30 details


Rf 88,2

Fidelity index Rf


Rg 96,0

Gamut index Rg


Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	83	-9%	-1%
2	85	-8%	5%
3	84	-4%	8%
4	91	2%	6%
5	94	3%	4%
6	94	3%	1%
7	90	-1%	-7%
8	97	-1%	-1%
9	92	-4%	-2%
10	91	-5%	1%
11	91	-2%	2%
12	90	0%	1%
13	89	2%	-11%
14	71	-1%	-20%
15	88	-2%	-9%
16	81	-11%	-9%




Hue binH



Color vector graphics




Hue bin



Color distortion graphics



Color Evaluation Sample



CLS LED BV
 info@cls-led.com
 www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

Glare Evaluation According to UGR

p Ceiling	70	70	50	50	30	70	70	50	50	30	
p Walls	50	30	50	30	30	50	30	50	30	30	
p Floor	20	20	20	20	20	20	20	20	20	20	
Room size X Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis					
2H	2H	12,0	12,5	12,1	12,7	12,9	12,0	12,5	12,1	12,7	12,9
	3H	12,3	12,9	12,6	13,1	13,3	12,3	12,9	12,6	13,1	13,3
	4H	12,4	13,0	12,8	13,2	13,4	12,4	13,0	12,8	13,2	13,4
	6H	12,5	13,0	12,8	13,3	13,6	12,5	13,0	12,8	13,3	13,6
	8H	12,5	13,0	12,8	13,3	13,7	12,5	13,0	12,8	13,3	13,7
	12H	12,4	12,9	12,8	13,3	13,7	12,4	12,9	12,8	13,3	13,7
4H	2H	12,0	12,6	12,4	12,9	13,1	12,0	12,6	12,4	12,9	13,1
	3H	12,6	13,1	12,9	13,4	13,8	12,6	13,1	12,9	13,4	13,8
	4H	12,7	13,1	13,1	13,6	14,1	12,7	13,1	13,1	13,6	14,1
	6H	12,8	13,3	13,3	13,6	13,9	12,8	13,3	13,3	13,6	13,9
	8H	12,8	13,2	13,3	13,6	13,9	12,8	13,2	13,3	13,6	13,9
	12H	12,7	13,1	13,2	13,5	13,9	12,7	13,1	13,2	13,5	13,9
8H	4H	12,7	13,1	13,2	13,5	13,8	12,7	13,1	13,2	13,5	13,8
	6H	12,8	13,1	13,3	13,6	14,1	12,8	13,1	13,3	13,6	14,1
	8H	12,9	13,1	13,4	13,6	14,3	12,9	13,1	13,4	13,6	14,3
	12H	12,9	13,1	13,5	13,6	14,2	12,9	13,1	13,5	13,6	14,2
12H	4H	12,6	13,0	13,1	13,4	13,8	12,6	13,0	13,1	13,4	13,8
	6H	12,9	13,1	13,4	13,6	14,2	12,9	13,1	13,4	13,6	14,2
	8H	12,9	13,0	13,4	13,6	14,2	12,9	13,0	13,4	13,6	14,2
Variation of the observer position for the luminaire distance S											
S = 1.0H	2,5 / -1,4					2,5 / -1,4					
S = 1.5H	4,5 / -1,9					4,5 / -1,9					
S = 2.0H	6,1 / -2,8					6,1 / -2,8					
Standard table	n/a					n/a					
Correction summand	n/a					n/a					
Corrected glare indices referring to 551lm total luminous flux											