

LM-79

Test Report

LM79-REVO-COMPACT-TRACK-3000K-CRI80-DEG8

General Discription

Item number	RC-X-X-03-5
Date and time	5-8-2016 11:32:56
CCT (Kelvin)	3011 K
Beam angle	12,8°
Luminous flux	681 lm
Efficiency	68 lm/watt
Weighted energy	10,0 kWh/1000h
Power factor	0,95
CRI (RA)	84,0
Fidelity index Rf	Rf 84,8
Gammut index Rg	Rg 96,7




CLS LED BV
info@cls-led.com
www.cls-led.com

2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-REVO-COMPACT-TRACK-3000K-CRI80-DEG8

Beam details		1m		2m		3m		4m		5m									
Lux*		9197 lx		2299 lx		1022 lx		575 lx		368 lx									
12,8° 																			
*measured at center of beam																			
Footcandles*		854,4 fcd		213,6 fcd		94,9 fcd		53,4 fcd		34,2 fcd									
Beam width (meter)		0,2 m		0,4 m		0,7 m		0,9 m		1,1 m									
Beam width (Feet)		0,7 ft		1,5 ft		2,2 ft		2,9 ft		3,7 ft									
Beam intensities																			
1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
9197lx	2299lx	1022lx	575lx	368lx	255lx	188lx	144lx	114lx	92lx	76lx	64lx	54lx	47lx	41lx	36lx	32lx	28lx	25lx	23lx
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
854,4fcd	213,6fcd	94,9fcd	53,4fcd	34,2fcd	23,7fcd	17,4fcd	13,4fcd	10,5fcd	8,5fcd	7,1fcd	5,9fcd	5,1fcd	4,4fcd	3,8fcd	3,3fcd	3fcd	2,6fcd	2,4fcd	2,1fcd
Intensities in 0° c-plane																			
0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
9197	9197	8951	8171	7207	6186	5165	4246	3473	2917	2397	1878	1456	1129	929	736	543	399	290	243
100%	100%	97%	89%	78%	67%	56%	46%	38%	32%	26%	20%	16%	12%	10%	8%	6%	4%	3%	3%
Intensities in 90° c-plane																			
0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
9197	9079	8214	7350	6485	5592	4740	4029	3318	2614	2117	1677	1365	1054	760	580	440	359	279	207
100%	99%	89%	80%	71%	61%	52%	44%	36%	28%	23%	18%	15%	11%	8%	6%	5%	4%	3%	2%
Intensities in 180° c-plane																			
0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
9197	9197	8951	8171	7207	6186	5165	4246	3473	2917	2397	1878	1456	1129	929	736	543	399	290	243
100%	100%	97%	89%	78%	67%	56%	46%	38%	32%	26%	20%	16%	12%	10%	8%	6%	4%	3%	3%
Intensities in 270° c-plane																			
0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
9197	9079	8214	7350	6485	5592	4740	4029	3318	2614	2117	1677	1365	1054	760	580	440	359	279	207
100%	99%	89%	80%	71%	61%	52%	44%	36%	28%	23%	18%	15%	11%	8%	6%	5%	4%	3%	2%
Beam angle 50%				Field angle 10%				Cutoff angle 2,5%				Intensity ratio in 120° cone				Intensity ratio in 90° cone			
12,8°				27,5°				{C_ANG}°				98,8%				97,8%			



CLS LED BV
info@cls-led.com
www.cls-led.com




2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-REVO-COMPACT-TRACK-3000K-CRI80-DEG8

Color details



CIE 1931

x: 0,437

3011 K


y: 0,404

Spectra

CIE 1931 ZOOM

Δuv : 0,0002


CRI: **84,0** (R1-R8)



CRI values, R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8
82,0	91,1	97,2	82,3	82,4	89,4	84,6	63,0
R9	R10	R11	R12	R13	R14	R15	
15,9	80,0	81,5	77,0	84,0	98,8	75,0	


CQS: **83,9**



CQS values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8
79,0	95,4	85,2	82,4	84,6	84,9	85,0	88,0
Q9	Q10	Q11	Q12	Q13	Q14	Q15	
95,8	90,5	87,4	85,1	84,0	74,0	75,5	

TM30: **84,8**



TM30 values, 16 binned values out of total of 99 values

C1	C2	C3	C4	C5	C6	C7	C8
79,7	80,6	77,0	87,0	92,6	92,2	85,9	92,4
C9	C10	C11	C12	C13	C14	C15	
89,7	84,1	83,2	85,6	87,8	80,9	78,6	

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3011 K	84,0	15,9	84,8	96,7	83,9	0,437	0,404	0,250	0,348	0,0002



CLS LED BV
info@cls-led.com
www.cls-led.com

2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-REVO-COMPACT-TRACK-3000K-CRI80-DEG8

TM30 details


Rf 84,8

Fidelity index Rf


Rg 96,7

Gamut index Rg


Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	80	-10%	-1%
2	81	-8%	6%
3	77	-3%	11%
4	87	2%	7%
5	93	3%	4%
6	92	3%	-2%
7	86	-2%	-8%
8	92	-3%	-2%
9	90	-6%	1%
10	84	-5%	6%
11	83	-1%	11%
12	86	5%	3%
13	88	5%	-6%
14	81	4%	-13%
15	79	-2%	-12%
16	79	-8%	-13%




Hue binH



Color vector graphics




Hue bin



Color distortion graphics



Color Evaluation Sample



CLS LED BV
info@cls-led.com
www.cls-led.com

2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-REVO-COMPACT-TRACK-3000K-CRI80-DEG8

Glare Evaluation According to UGR

p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	7,0	7,6	7,2	7,8	8,0	6,5	7,2	6,8	7,4	7,6
	3H	7,3	7,9	7,6	8,1	8,4	6,9	7,5	7,2	7,8	8,0
	4H	7,5	8,1	7,8	8,3	8,6	7,1	7,6	7,4	7,9	8,2
	6H	7,7	8,2	8,1	8,5	8,8	7,3	7,8	7,6	8,1	8,4
	8H	7,9	8,4	8,2	8,7	9,0	7,4	7,8	7,7	8,1	8,5
	12H	8,1	8,6	8,4	8,9	9,2	7,4	7,9	7,8	8,2	8,5
4H	2H	7,1	7,6	7,4	7,9	8,2	6,7	7,2	7,0	7,5	7,8
	3H	7,5	8,0	7,9	8,3	8,6	7,2	7,7	7,6	8,0	8,3
	4H	7,9	8,3	8,3	8,6	9,0	7,5	7,9	7,8	8,2	8,6
	6H	8,2	8,6	8,6	8,9	9,3	7,8	8,1	8,2	8,5	8,9
	8H	8,5	8,8	8,9	9,2	9,6	7,9	8,2	8,4	8,6	9,0
	12H	8,8	9,0	9,2	9,5	9,9	8,1	8,3	8,5	8,7	9,2
8H	4H	7,9	8,2	8,4	8,6	9,0	7,6	7,9	8,0	8,2	8,7
	6H	8,5	8,7	8,9	9,1	9,6	8,0	8,3	8,5	8,7	9,1
	8H	8,8	9,0	9,3	9,5	9,9	8,3	8,4	8,7	8,9	9,4
	12H	9,3	9,4	9,8	9,9	10,4	8,5	8,7	9,0	9,1	9,6
12H	4H	7,9	8,2	8,4	8,6	9,0	7,6	7,8	8,0	8,2	8,7
	6H	8,5	8,7	9,0	9,1	9,6	8,1	8,3	8,6	8,7	9,2
	8H	8,9	9,1	9,4	9,5	10,0	8,4	8,5	8,9	9,0	9,5

Variation of the observer position for the luminaire distance S

S = 1,0H	+0,9 / -0,8	+1,0 / -0,9
S = 1,5H	+2,1 / -1,3	+2,3 / -1,8
S = 2,0H	+3,5 / -2,4	+3,8 / -1,9
Standard table	BK03	BK03
Correction summand	-9,0	-9,5

Corrected glare indices referring to 681lm total luminous flux



CLS LED BV
info@cls-led.com
www.cls-led.com

2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf