

LM-79

Test Report


LM79-REVO-MICRO-BASIC-3000K-CRI80-30DEG

General Discription


Item number	RM-2-X-03-3
Date and time	12-11-2018 12:36:58
CCT (Kelvin)	2903 K
Beam angle	31,4°
Luminous flux	333 lm
Efficiency	0 lm/watt
Weighted energy	- kWh/1000h
Power factor	n/a
CRI (RA)	84,5
Fidelity index Rf	Rf 84,1
Gammut index Rg	Rg 98,3
Peak	867 cd



Polar diagram



Cartesian diagram



CLS LED BV
info@cls-led.com
www.cls-led.com

2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-REVO-MICRO-BASIC-3000K-CRI80-30DEG

Beam details	1m	2m	3m	4m	5m
Lux*	867 lx	217 lx	96 lx	54 lx	35 lx

*measured at center of beam

Footcandles*	80,6 fcd	20,1 fcd	9,0 fcd	5,0 fcd	3,2 fcd
Beam width (meter)	0,6 m	1,1 m	1,7 m	2,2 m	2,8 m
Beam width (Feet)	1,8 ft	3,7 ft	5,5 ft	7,4 ft	9,2 ft

Beam intensities																			
1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
867lx	217lx	96lx	54lx	35lx	24lx	18lx	14lx	11lx	9lx	7lx	6lx	5lx	4lx	4lx	3lx	3lx	3lx	2lx	2lx
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
80,6fcd	20,1fcd	9fcd	5fcd	3,2fcd	2,2fcd	1,6fcd	1,3fcd	1fcd	0,8fcd	0,7fcd	0,6fcd	0,5fcd	0,4fcd	0,4fcd	0,3fcd	0,3fcd	0,2fcd	0,2fcd	0,2fcd

Intensities in 0° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
867	858	830	785	726	656	579	499	422	351	287	232	184	145	113	88	68	52	41	31
100%	99%	96%	90%	84%	76%	67%	58%	49%	40%	33%	27%	21%	17%	13%	10%	8%	6%	5%	4%

Intensities in 90° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
867	858	830	785	726	656	579	499	422	351	287	232	184	145	113	88	68	52	41	31
100%	99%	96%	90%	84%	76%	67%	58%	49%	40%	33%	27%	21%	17%	13%	10%	8%	6%	5%	4%

Intensities in 180° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
867	858	830	785	726	656	579	499	422	351	287	232	184	145	113	88	68	52	41	31
100%	99%	96%	90%	84%	76%	67%	58%	49%	40%	33%	27%	21%	17%	13%	10%	8%	6%	5%	4%

Intensities in 270° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
867	858	830	785	726	656	579	499	422	351	287	232	184	145	113	88	68	52	41	31
100%	99%	96%	90%	84%	76%	67%	58%	49%	40%	33%	27%	21%	17%	13%	10%	8%	6%	5%	4%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
31,4°	60,2°	82,1°	96,6%	93,6%



CLS LED BV
 info@cls-led.com
 www.cls-led.com




2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-REVO-MICRO-BASIC-3000K-CRI80-30DEG

Color details



CIE 1931

x: 0,444

2903 K


y: 0,405

Spectra

CIE 1931 ZOOM

Δuv : -0,0004


CRI: 84,5 (R1-R8)



CRI values, R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8
82,6	90,7	97,2	83,2	82,7	88,7	85,4	65,2
R9	R10	R11	R12	R13	R14	R15	
21,5	79,1	82,5	76,7	84,2	98,5	76,3	


CQS: 83,4



CQS values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8
78,5	95,9	84,2	82,5	84,1	83,2	83,5	86,6
Q9	Q10	Q11	Q12	Q13	Q14	Q15	
95,9	89,0	86,1	84,1	83,6	74,8	75,8	

TM30: 84,1



TM30 values, 16 binned values out of total of 99 values

C1	C2	C3	C4	C5	C6	C7	C8
80,7	80,8	75,3	84,6	89,2	89,4	82,7	91,2
C9	C10	C11	C12	C13	C14	C15	
88,6	86,2	82,8	84,6	87,9	81,9	81,8	

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2903 K	84,5	21,5	84,1	98,3	83,4	0,444	0,405	0,254	0,349	-0,0004



CLS LED BV
info@cls-led.com
www.cls-led.com

2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

Test Report

LM79-REVO-MICRO-BASIC-3000K-CRI80-30DEG

TM30 details


Rf 84,1

Fidelity index R_f


Rg 98,3

Gammut index Rg


		Graphic shifts (%)	
Hue Bin	R_f	Chroma	Hue
1	81	-10%	-2%
2	81	-7%	7%
3	75	-2%	12%
4	85	4%	9%
5	89	6%	5%
6	89	5%	-3%
7	83	1%	-10%
8	91	-2%	-4%
9	89	-6%	-1%
10	86	-6%	5%
11	83	-3%	10%
12	85	5%	4%
13	88	6%	-5%
14	82	5%	-12%
15	82	0%	-10%
16	79	-7%	-13%




Hue binH




Color vector graphics




Hue bin



Color distortion graphics



Color Evaluation Sample



CLS LED BV
info@cls-led.com
www.cls-led.com

2017 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

Glare Evaluation According to UGR

p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	9,8	10,5	10,1	10,7	10,9	9,8	10,5	10,1	10,7	10,9
	3H	10,1	10,7	10,4	11,0	11,2	10,1	10,7	10,4	11,0	11,2
	4H	10,2	10,8	10,6	11,1	11,4	10,2	10,8	10,6	11,1	11,4
	6H	10,4	10,9	10,7	11,2	11,6	10,4	10,9	10,7	11,2	11,6
	8H	10,5	11,0	10,9	11,3	11,7	10,5	11,0	10,9	11,3	11,7
	12H	10,6	11,1	11,0	11,5	11,8	10,6	11,1	11,0	11,5	11,8
4H	2H	9,8	10,4	10,2	10,7	11,0	9,8	10,4	10,2	10,7	11,0
	3H	10,3	10,8	10,6	11,1	11,4	10,3	10,8	10,6	11,1	11,4
	4H	10,5	10,9	10,9	11,3	11,7	10,5	10,9	10,9	11,3	11,7
	6H	10,8	11,1	11,2	11,5	11,9	10,8	11,1	11,2	11,5	11,9
	8H	11,0	11,3	11,4	11,7	12,1	11,0	11,3	11,4	11,7	12,1
	12H	11,2	11,5	11,7	11,9	12,4	11,2	11,5	11,7	11,9	12,4
8H	4H	10,6	10,9	11,0	11,3	11,7	10,6	10,9	11,0	11,3	11,7
	6H	11,0	11,2	11,4	11,6	12,1	11,0	11,2	11,4	11,6	12,1
	8H	11,2	11,4	11,7	11,9	12,4	11,2	11,4	11,7	11,9	12,4
	12H	11,6	11,8	12,1	12,3	12,8	11,6	11,8	12,1	12,3	12,8
12H	4H	10,6	10,8	11,0	11,3	11,7	10,6	10,8	11,0	11,3	11,7
	6H	11,0	11,2	11,5	11,7	12,2	11,0	11,2	11,5	11,7	12,2
	8H	11,3	11,5	11,8	12,0	12,5	11,3	11,5	11,8	12,0	12,5
Variation of the observer position for the luminaire distance S											
S = 1,0H		+2,2 / -1,4					+2,2 / -1,4				
S = 1,5H		+4,2 / -1,9					+4,2 / -1,9				
S = 2,0H		+6,0 / -2,4					+6,0 / -2,4				
Standard table		BK03					BK03				
Correction summand		-6,5					-6,5				
Corrected glare indices referring to 333lm total luminous flux											