

LM-79

Test Report


LM79-RUBY-COMPACT-2700K-CRI90-SPOT

General Discription


Item number	
Date and time	24-3-2021 14:16:53
CCT (Kelvin)	2740 K
Beam angle	18,3°
Luminous flux	2524 lm
Efficiency	90 lm/watt
Weighted energy	28,2 kWh/1000h
Power factor	0,97
CRI (RA)	92,5
Fidelity index Rf	Rf 91,5
Gammut index Rg	Rg 97,9
Peak	13597 cd



Polar diagram



Cartesian diagram




CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-RUBY-COMPACT-2700K-CRI90-SPOT

Beam details				1m		2m		3m		4m		5m											
Lux*				13597 lx		3399 lx		1511 lx		850 lx		544 lx											
18,3° 																							
*measured at center of beam																							
Footcandles*				1263,2 fcd		315,8 fcd		140,4 fcd		79,0 fcd		50,5 fcd											
Beam width (meter)				0,3 m		0,6 m		1 m		1,3 m		1,6 m											
Beam width (Feet)				1,1 ft		2,1 ft		3,2 ft		4,2 ft		5,3 ft											
Beam intensities																							
1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m				
13597lx	3399lx	1511lx	850lx	544lx	378lx	277lx	212lx	168lx	136lx	112lx	94lx	80lx	69lx	60lx	53lx	47lx	42lx	38lx	34lx				
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft				
1263,2fcd	315,8fcd	140,4fcd	79fcd	50,5fcd	35,1fcd	25,8fcd	19,7fcd	15,6fcd	12,6fcd	10,4fcd	8,8fcd	7,5fcd	6,4fcd	5,6fcd	4,9fcd	4,4fcd	3,9fcd	3,5fcd	3,2fcd				
Intensities in 0° c-plane																							
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°				
13,6K	13,2K	11,9K	10,1K	8,0K	6,0K	4,3K	3,0K	2,2K	1,7K	1,4K	1,2K	1,1K	1,0K	0,9K	0,8K	0,7K	0,6K	0,4K	0,3K				
100%	97%	88%	74%	59%	44%	31%	22%	16%	12%	10%	9%	8%	7%	7%	6%	5%	4%	3%	2%				
Intensities in 90° c-plane																							
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°				
13,6K	13,2K	11,9K	10,1K	8,0K	6,0K	4,3K	3,0K	2,2K	1,7K	1,4K	1,2K	1,1K	1,0K	0,9K	0,8K	0,7K	0,6K	0,4K	0,3K				
100%	97%	88%	74%	59%	44%	31%	22%	16%	12%	10%	9%	8%	7%	7%	6%	5%	4%	3%	2%				
Intensities in 180° c-plane																							
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°				
13,6K	13,2K	11,9K	10,1K	8,0K	6,0K	4,3K	3,0K	2,2K	1,7K	1,4K	1,2K	1,1K	1,0K	0,9K	0,8K	0,7K	0,6K	0,4K	0,3K				
100%	97%	88%	74%	59%	44%	31%	22%	16%	12%	10%	9%	8%	7%	7%	6%	5%	4%	3%	2%				
Intensities in 270° c-plane																							
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°				
13,6K	13,2K	11,9K	10,1K	8,0K	6,0K	4,3K	3,0K	2,2K	1,7K	1,4K	1,2K	1,1K	1,0K	0,9K	0,8K	0,7K	0,6K	0,4K	0,3K				
100%	97%	88%	74%	59%	44%	31%	22%	16%	12%	10%	9%	8%	7%	7%	6%	5%	4%	3%	2%				
Beam angle 50%				Field angle 10%				Cutoff angle 2,5%				Intensity ratio in 120° cone				Intensity ratio in 90° cone							
18,3°				40,5°				74,3°				99,6%				98,2%							



CLS LED BV
info@cls-led.com
www.cls-led.com




2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-RUBY-COMPACT-2700K-CRI90-SPOT

Color details



CIE 1931

x: 0,457

2740 K

y: 0,410


Spectra

CIE 1931 ZOOM

 $\Delta uv: -0,0001$

CRI: 92,5 (R1-R8)


CRI values, R1-R8 are used to calculate final CRI value



R1	R2	R3	R4	R5	R6	R7	R8
92,8	97,2	98,7	92,5	92,8	96,9	90,3	79,1
R9	R10	R11	R12	R13	R14	R15	
55,1	92,9	94,1	83,9	94,1	99,6	87,6	

CQS: 90,6


CQS values



Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8
86,9	94,4	90,3	89,0	91,2	92,4	92,1	92,4
Q9	Q10	Q11	Q12	Q13	Q14	Q15	
96,2	94,8	93,7	92,4	91,5	85,5	85,9	

TM30: 91,5

TM30 values, 16 binned values out of total of 99 values



C1	C2	C3	C4	C5	C6	C7	C8
89,5	91,6	91,1	94,3	95,5	96,8	94,0	96,8
C9	C10	C11	C12	C13	C14	C15	
92,9	89,9	89,8	89,9	90,3	86,9	91,1	

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2740 K	92,5	55,1	91,5	97,9	90,6	0,457	0,410	0,261	0,351	-0,0001



CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-RUBY-COMPACT-2700K-CRI90-SPOT

TM30 details


Rf 91,5

Fidelity index Rf


Rg 97,9

Gamut index Rg


Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	89	-6%	1%
2	92	-4%	3%
3	91	-2%	4%
4	94	-2%	1%
5	95	-1%	2%
6	97	0%	0%
7	94	-3%	-1%
8	97	-1%	1%
9	93	-2%	4%
10	90	0%	7%
11	90	2%	7%
12	90	5%	-1%
13	90	2%	-7%
14	87	3%	-10%
15	91	-3%	-4%
16	85	-4%	-11%




Hue binH



Color vector graphics




Hue bin



Color distortion graphics



Color Evaluation Sample



CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

Glare Evaluation According to UGR

p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	19,1	19,5	19,1	19,7	19,9	19,1	19,5	19,1	19,7	19,9
	3H	18,8	19,4	19,1	19,6	19,8	18,8	19,4	19,1	19,6	19,8
	4H	18,7	19,3	19,1	19,5	19,8	18,7	19,3	19,1	19,5	19,8
	6H	18,7	19,2	19,0	19,5	19,8	18,7	19,2	19,0	19,5	19,8
	8H	18,6	19,1	19,0	19,5	19,8	18,6	19,1	19,0	19,5	19,8
	12H	18,6	19,1	18,9	19,4	19,8	18,6	19,1	18,9	19,4	19,8
4H	2H	18,7	19,3	19,1	19,5	19,8	18,7	19,3	19,1	19,5	19,8
	3H	18,6	19,1	19,0	19,4	19,8	18,6	19,1	19,0	19,4	19,8
	4H	18,5	18,9	18,9	19,3	19,8	18,5	18,9	18,9	19,3	19,8
	6H	18,4	18,9	18,9	19,2	19,5	18,4	18,9	18,9	19,2	19,5
	8H	18,3	18,8	18,9	19,1	19,5	18,3	18,8	18,9	19,1	19,5
	12H	18,3	18,6	18,8	19,0	19,5	18,3	18,6	18,8	19,0	19,5
8H	4H	18,3	18,8	18,8	19,1	19,5	18,3	18,8	18,8	19,1	19,5
	6H	18,3	18,6	18,8	19,0	19,5	18,3	18,6	18,8	19,0	19,5
	8H	18,3	18,5	18,8	19,0	19,6	18,3	18,5	18,8	19,0	19,6
	12H	18,2	18,4	18,8	18,9	19,5	18,2	18,4	18,8	18,9	19,5
12H	4H	18,3	18,6	18,8	19,0	19,5	18,3	18,6	18,8	19,0	19,5
	6H	18,3	18,5	18,8	19,0	19,6	18,3	18,5	18,8	19,0	19,6
	8H	18,2	18,4	18,8	18,9	19,5	18,2	18,4	18,8	18,9	19,5
Variation of the observer position for the luminaire distance S											
S = 1.0H		5,5 / -9,0					5,5 / -9,0				
S = 1.5H		8,2 / -11,6					8,2 / -11,6				
S = 2.0H		10,2 / -13,2					10,2 / -13,2				
Standard table		n/a					n/a				
Correction summand		n/a					n/a				
Corrected glare indices referring to 2524lm total luminous flux											