

LM-79

Test Report


LM79-RUBY-COMPACT-3000K-CRI90-SPOT

General Discription


Item number	
Date and time	24-3-2021 14:11:45
CCT (Kelvin)	3099 K
Beam angle	18,5°
Luminous flux	2619 lm
Efficiency	95 lm/watt
Weighted energy	27,7 kWh/1000h
Power factor	0,97
CRI (RA)	92,6
Fidelity index Rf	Rf 91,0
Gammut index Rg	Rg 98,1
Peak	13798 cd



Polar diagram



Cartesian diagram




CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-RUBY-COMPACT-3000K-CRI90-SPOT

Beam details		1m		2m		3m		4m		5m									
Lux*		13798 lx		3450 lx		1533 lx		862 lx		552 lx									
18,5° 																			
*measured at center of beam																			
Footcandles*		1281,9 fcd		320,5 fcd		142,4 fcd		80,1 fcd		51,3 fcd									
Beam width (meter)		0,3 m		0,7 m		1 m		1,3 m		1,6 m									
Beam width (Feet)		1,1 ft		2,1 ft		3,2 ft		4,3 ft		5,3 ft									
Beam intensities																			
1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
13798lx	3450lx	1533lx	862lx	552lx	383lx	282lx	216lx	170lx	138lx	114lx	96lx	82lx	70lx	61lx	54lx	48lx	43lx	38lx	34lx
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
1281,9fcd	320,5fcd	142,4fcd	80,1fcd	51,3fcd	35,6fcd	26,2fcd	20fcd	15,8fcd	12,8fcd	10,6fcd	8,9fcd	7,6fcd	6,5fcd	5,7fcd	5fcd	4,4fcd	4fcd	3,6fcd	3,2fcd
Intensities in 0° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
13,8K	13,4K	12,1K	10,3K	8,2K	6,2K	4,5K	3,2K	2,3K	1,8K	1,5K	1,3K	1,1K	1,0K	1,0K	0,9K	0,7K	0,6K	0,4K	0,3K
100%	97%	88%	74%	59%	45%	32%	23%	17%	13%	11%	9%	8%	8%	7%	6%	5%	4%	3%	2%
Intensities in 90° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
13,8K	13,4K	12,1K	10,3K	8,2K	6,2K	4,5K	3,2K	2,3K	1,8K	1,5K	1,3K	1,1K	1,0K	1,0K	0,9K	0,7K	0,6K	0,4K	0,3K
100%	97%	88%	74%	59%	45%	32%	23%	17%	13%	11%	9%	8%	8%	7%	6%	5%	4%	3%	2%
Intensities in 180° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
13,8K	13,4K	12,1K	10,3K	8,2K	6,2K	4,5K	3,2K	2,3K	1,8K	1,5K	1,3K	1,1K	1,0K	1,0K	0,9K	0,7K	0,6K	0,4K	0,3K
100%	97%	88%	74%	59%	45%	32%	23%	17%	13%	11%	9%	8%	8%	7%	6%	5%	4%	3%	2%
Intensities in 270° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
13,8K	13,4K	12,1K	10,3K	8,2K	6,2K	4,5K	3,2K	2,3K	1,8K	1,5K	1,3K	1,1K	1,0K	1,0K	0,9K	0,7K	0,6K	0,4K	0,3K
100%	97%	88%	74%	59%	45%	32%	23%	17%	13%	11%	9%	8%	8%	7%	6%	5%	4%	3%	2%
Beam angle 50%				Field angle 10%				Cutoff angle 2,5%				Intensity ratio in 120° cone				Intensity ratio in 90° cone			
18,5°				41,3°				74,6°				99,6%				98,1%			



CLS LED BV
info@cls-led.com
www.cls-led.com




2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-RUBY-COMPACT-3000K-CRI90-SPOT

Color details



CIE 1931

x: 0,431



Spectra

CIE 1931 ZOOM


3099 K

y: 0,402

Δuv : 0,0003

CRI: 92,6 (R1-R8)


CRI values, R1-R8 are used to calculate final CRI value



R1	R2	R3	R4	R5	R6	R7	R8
92,7	96,6	98,6	92,4	92,3	95,4	91,8	81,3
R9	R10	R11	R12	R13	R14	R15	
57,6	91,1	93,3	78,5	93,9	98,9	88,4	

CQS: 90,8


CQS values



Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8
88,1	95,7	88,9	87,4	90,4	92,0	92,4	93,2
Q9	Q10	Q11	Q12	Q13	Q14	Q15	
97,5	94,9	93,7	92,9	92,3	86,5	87,2	

TM30: 91,0

TM30 values, 16 binned values out of total of 99 values



C1	C2	C3	C4	C5	C6	C7	C8
89,8	92,0	91,2	94,4	93,2	96,9	92,3	96,2
C9	C10	C11	C12	C13	C14	C15	
91,7	86,7	87,7	90,0	91,9	87,5	88,2	

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3099 K	92,6	57,6	91,0	98,1	90,8	0,431	0,402	0,247	0,347	0,0003



CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-RUBY-COMPACT-3000K-CRI90-SPOT

TM30 details


Rf 91,0

Fidelity index Rf


Rg 98,1

Gamut index Rg


Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	90	-5%	1%
2	92	-3%	2%
3	91	-2%	4%
4	94	-2%	1%
5	93	-4%	1%
6	97	0%	0%
7	92	-4%	0%
8	96	-2%	1%
9	92	-2%	5%
10	87	-1%	8%
11	88	2%	8%
12	90	6%	0%
13	92	2%	-5%
14	87	4%	-9%
15	88	-2%	-6%
16	85	-2%	-11%




Hue binH



Color vector graphics




Hue bin



Color distortion graphics



Color Evaluation Sample



CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-RUBY-COMPACT-3000K-CRI90-SPOT

Glare Evaluation According to UGR

p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	19,2	19,7	19,3	19,9	20,1	19,2	19,7	19,3	19,9	20,1
	3H	18,9	19,6	19,3	19,8	19,9	18,9	19,6	19,3	19,8	19,9
	4H	18,9	19,5	19,3	19,7	19,9	18,9	19,5	19,3	19,7	19,9
	6H	18,9	19,4	19,2	19,7	20,0	18,9	19,4	19,2	19,7	20,0
	8H	18,8	19,3	19,1	19,6	20,0	18,8	19,3	19,1	19,6	20,0
	12H	18,8	19,2	19,1	19,6	20,0	18,8	19,2	19,1	19,6	20,0
4H	2H	18,9	19,5	19,3	19,7	19,9	18,9	19,5	19,3	19,7	19,9
	3H	18,8	19,2	19,1	19,6	20,0	18,8	19,2	19,1	19,6	20,0
	4H	18,6	19,1	19,1	19,5	20,0	18,6	19,1	19,1	19,5	20,0
	6H	18,6	19,0	19,1	19,4	19,7	18,6	19,0	19,1	19,4	19,7
	8H	18,5	18,9	19,0	19,3	19,6	18,5	18,9	19,0	19,3	19,6
	12H	18,4	18,8	18,9	19,2	19,6	18,4	18,8	18,9	19,2	19,6
8H	4H	18,5	18,9	19,0	19,3	19,6	18,5	18,9	19,0	19,3	19,6
	6H	18,4	18,7	18,9	19,2	19,7	18,4	18,7	18,9	19,2	19,7
	8H	18,4	18,7	18,9	19,2	19,8	18,4	18,7	18,9	19,2	19,8
	12H	18,4	18,6	19,0	19,1	19,7	18,4	18,6	19,0	19,1	19,7
12H	4H	18,4	18,8	18,9	19,2	19,6	18,4	18,8	18,9	19,2	19,6
	6H	18,4	18,6	18,9	19,2	19,8	18,4	18,6	18,9	19,2	19,8
	8H	18,4	18,6	19,0	19,1	19,7	18,4	18,6	19,0	19,1	19,7
Variation of the observer position for the luminaire distance S											
S = 1.0H		5,5 / -8,8					5,5 / -8,8				
S = 1.5H		8,2 / -11,1					8,2 / -11,1				
S = 2.0H		10,1 / -13,0					10,1 / -13,0				
Standard table		n/a					n/a				
Correction summand		n/a					n/a				
Corrected glare indices referring to 2619lm total luminous flux											



CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf