



General Discription

Item number	T-C-XCX-1C-N370-F
Date and time	8-12-2025 17:10:03
CCT (Kelvin)	3315 K
Beam angle	53,6°
Luminous flux	577 lm
Efficiency	51 lm/watt
Weighted energy	11,3 kWh/1000h
Power factor	0,47
CRI (RA)	86,5
Fidelity index Rf	Rf 86,7
Gammut index Rg	Rg 99,0
Peak	749 cd



Polar curve



Linear distribution diagram

LM-79

Test Report

LM79-TOPAZ-COLOURFLOW-RGB3-FLOOD [3000K]

Beam details	1m	2m	3m	4m	5m
Lux*	744 lx	186 lx	83 lx	47 lx	30 lx

*measured at center of beam

Footcandles*	69,2 fcd	17,3 fcd	7,7 fcd	4,3 fcd	2,8 fcd
Beam width (meter)	1 m	2 m	3 m	4 m	5 m
Beam width (Feet)	3,3 ft	6,6 ft	9,9 ft	13,3 ft	16,6 ft

Beam intensities																			
1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
744lx	186lx	83lx	47lx	30lx	21lx	15lx	12lx	9lx	7lx	6lx	5lx	4lx	4lx	3lx	3lx	3lx	2lx	2lx	2lx
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
69,2fcd	17,3fcd	7,7fcd	4,3fcd	2,8fcd	1,9fcd	1,4fcd	1,1fcd	0,9fcd	0,7fcd	0,6fcd	0,5fcd	0,4fcd	0,4fcd	0,3fcd	0,3fcd	0,2fcd	0,2fcd	0,2fcd	0,2fcd

Intensities in 0° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
744	748	748	742	733	723	704	678	651	617	576	526	467	402	333	267	208	157	116	84
100%	100%	101%	100%	99%	97%	95%	91%	87%	83%	77%	71%	63%	54%	45%	36%	28%	21%	16%	11%

Intensities in 90° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
744	748	748	742	733	723	704	678	651	617	576	526	467	402	333	267	208	157	116	84
100%	100%	101%	100%	99%	97%	95%	91%	87%	83%	77%	71%	63%	54%	45%	36%	28%	21%	16%	11%

Intensities in 180° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
744	748	748	742	733	723	704	678	651	617	576	526	467	402	333	267	208	157	116	84
100%	100%	101%	100%	99%	97%	95%	91%	87%	83%	77%	71%	63%	54%	45%	36%	28%	21%	16%	11%

Intensities in 270° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
744	748	748	742	733	723	704	678	651	617	576	526	467	402	333	267	208	157	116	84
100%	100%	101%	100%	99%	97%	95%	91%	87%	83%	77%	71%	63%	54%	45%	36%	28%	21%	16%	11%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
53,6°	77,5°	96,5°	98,9%	96,1%



CLS LED BV
 info@cls-led.com
 www.cls-led.com




2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-TOPAZ-COLOURFLOW-RGB3-FLOOD [3000K]

Color details



CIE 1931

x: 0,413



Spectra


CIE 1931 ZOOM

3315 K

y: 0,387

Δuv : -0,0030


CRI: 86,5 (R1-R8)



CRI values, R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8
86,1	92,7	96,7	86,3	86,4	90,9	85,7	67,4
R9	R10	R11	R12	R13	R14	R15	
23,4	82,7	86,8	78,3	87,8	98,4	79,4	


CQS: 84,6



CQS values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8
81,2	97,6	83,0	82,5	86,3	86,7	86,0	88,3
Q9	Q10	Q11	Q12	Q13	Q14	Q15	
97,4	89,1	86,6	84,8	84,7	75,8	77,5	

TM30: 86,7



TM30 values, 16 binned values out of total of 99 values

C1	C2	C3	C4	C5	C6	C7	C8
83,6	84,3	79,6	87,4	91,3	91,3	90,7	93,8
C9	C10	C11	C12	C13	C14	C15	
92,3	86,8	82,6	87,9	89,8	84,2	82,9	

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3315 K	86,5	23,4	86,7	99,0	84,6	0,413	0,387	0,242	0,341	-0,0030



CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-TOPAZ-COLOURFLOW-RGB3-FLOOD [3000K]

TM30 details


Rf 86,7

Fidelity index Rf


Rg 99,0

Gamut index Rg


Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	84	-10%	-1%
2	84	-7%	6%
3	80	-2%	11%
4	87	3%	8%
5	91	5%	4%
6	91	5%	-2%
7	91	0%	-6%
8	94	-1%	-3%
9	92	-5%	1%
10	87	-6%	6%
11	83	0%	11%
12	88	6%	3%
13	90	5%	-4%
14	84	6%	-11%
15	83	-1%	-12%
16	83	-5%	-11%




Hue binH




Color vector graphics




Hue bin



Color distortion graphics



Color Evaluation Sample



CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-TOPAZ-COLOURFLOW-RGB3-FLOOD [3000K]

Glare Evaluation According to UGR

p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	14,1	14,7	14,2	14,9	15,1	14,1	14,7	14,2	14,9	15,1
	3H	13,8	14,6	14,2	14,8	15,0	13,8	14,6	14,2	14,8	15,0
	4H	13,8	14,5	14,2	14,7	15,0	13,8	14,5	14,2	14,7	15,0
	6H	13,8	14,4	14,1	14,7	15,0	13,8	14,4	14,1	14,7	15,0
	8H	13,7	14,3	14,1	14,6	15,0	13,7	14,3	14,1	14,6	15,0
	12H	13,7	14,2	14,0	14,6	15,0	13,7	14,2	14,0	14,6	15,0
4H	2H	13,8	14,5	14,1	14,7	14,9	13,8	14,5	14,1	14,7	14,9
	3H	13,7	14,2	14,0	14,6	15,0	13,7	14,2	14,0	14,6	15,0
	4H	13,6	14,1	14,0	14,5	15,0	13,6	14,1	14,0	14,5	15,0
	6H	13,5	14,1	14,0	14,4	14,7	13,5	14,1	14,0	14,4	14,7
	8H	13,5	14,0	14,0	14,3	14,7	13,5	14,0	14,0	14,3	14,7
	12H	13,4	13,8	13,9	14,2	14,7	13,4	13,8	13,9	14,2	14,7
8H	4H	13,4	14,0	14,0	14,3	14,7	13,4	14,0	14,0	14,3	14,7
	6H	13,4	13,7	13,9	14,2	14,7	13,4	13,7	13,9	14,2	14,7
	8H	13,4	13,7	13,9	14,2	14,8	13,4	13,7	13,9	14,2	14,8
	12H	13,4	13,6	13,9	14,1	14,7	13,4	13,6	13,9	14,1	14,7
12H	4H	13,4	13,8	13,9	14,2	14,6	13,4	13,8	13,9	14,2	14,6
	6H	13,4	13,7	13,9	14,2	14,8	13,4	13,7	13,9	14,2	14,8
	8H	13,3	13,6	13,9	14,1	14,7	13,3	13,6	13,9	14,1	14,7
Variation of the observer position for the luminaire distance S											
S = 1.0H		5,3 / -8,1					5,3 / -8,1				
S = 1.5H		8,0 / -9,8					8,0 / -9,8				
S = 2.0H		10,0 / -10,7					10,0 / -10,7				
Standard table		n/a					n/a				
Correction summand		n/a					n/a				
Corrected glare indices referring to 577lm total luminous flux											



CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf