


LM-79

Test Report


LM79-TOPAZ-COLOURFLOW-RGB3-MEDIUM [GREEN]

General Discription

Item number	T-C-XCX-1C-N370-M
Date and time	8-12-2025 13:57:50
CCT (Kelvin)	0 K
Beam angle	24,5°
Luminous flux	618 lm
Efficiency	59 lm/watt
Weighted energy	10,5 kWh/1000h
Power factor	0,48
CRI (RA)	0,0
Fidelity index Rf	Rf 0,0
Gammut index Rg	Rg 0,0
Peak	2623 cd



Polar curve



Linear distribution diagram




CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-TOPAZ-COLOURFLOW-RGB3-MEDIUM
[GREEN]

Beam details					1m		2m		3m		4m		5m							
Lux*					2623 lx		656 lx		291 lx		164 lx		105 lx							
24,5° 																				
*measured at center of beam																				
Footcandles*					243,7 fcd		60,9 fcd		27,1 fcd		15,2 fcd		9,7 fcd							
Beam width (meter)					0,4 m		0,9 m		1,3 m		1,7 m		2,2 m							
Beam width (Feet)					1,4 ft		2,8 ft		4,3 ft		5,7 ft		7,1 ft							
Beam intensities																				
1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m	
2623lx	656lx	291lx	164lx	105lx	73lx	54lx	41lx	32lx	26lx	22lx	18lx	16lx	13lx	12lx	10lx	9lx	8lx	7lx	7lx	
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft	
243,7fcd	60,9fcd	27,1fcd	15,2fcd	9,7fcd	6,8fcd	5fcd	3,8fcd	3fcd	2,4fcd	2fcd	1,7fcd	1,4fcd	1,2fcd	1,1fcd	1fcd	0,8fcd	0,8fcd	0,7fcd	0,6fcd	
Intensities in 0° c-plane																				
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	
2623	2569	2413	2187	1917	1628	1345	1081	845	640	472	343	246	176	127	93	70	53	41	33	
100%	98%	92%	83%	73%	62%	51%	41%	32%	24%	18%	13%	9%	7%	5%	4%	3%	2%	2%	1%	
Intensities in 90° c-plane																				
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	
2623	2569	2413	2187	1917	1628	1345	1081	845	640	472	343	246	176	127	93	70	53	41	33	
100%	98%	92%	83%	73%	62%	51%	41%	32%	24%	18%	13%	9%	7%	5%	4%	3%	2%	2%	1%	
Intensities in 180° c-plane																				
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	
2623	2569	2413	2187	1917	1628	1345	1081	845	640	472	343	246	176	127	93	70	53	41	33	
100%	98%	92%	83%	73%	62%	51%	41%	32%	24%	18%	13%	9%	7%	5%	4%	3%	2%	2%	1%	
Intensities in 270° c-plane																				
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	
2623	2569	2413	2187	1917	1628	1345	1081	845	640	472	343	246	176	127	93	70	53	41	33	
100%	98%	92%	83%	73%	62%	51%	41%	32%	24%	18%	13%	9%	7%	5%	4%	3%	2%	2%	1%	
Beam angle 50%					Field angle 10%				Cutoff angle 2,5%				Intensity ratio in 120° cone				Intensity ratio in 90° cone			
24,5°					47,2°				64,8°				99,0%				97,2%			



CLS LED BV
info@cls-led.com
www.cls-led.com




2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-TOPAZ-COLOURFLOW-RGB3-MEDIUM
[GREEN]

Color details



CIE 1931

x: 0,175



Spectra

CIE 1931 ZOOM

0 K

y: 0,708

 Δuv : n/a

CRI: 0,0 (R1-R8)

CRI values, R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8
0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0
R9	R10	R11	R12	R13	R14	R15	
0,0	0,0	0,0	0,0	0,0	0,0	0,0	

CQS: 0,0

CQS values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8
0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0
Q9	Q10	Q11	Q12	Q13	Q14	Q15	
0,0	0,0	0,0	0,0	0,0	0,0	0,0	

TM30: 0,0

TM30 values, 16 binned values out of total of 99 values

C1	C2	C3	C4	C5	C6	C7	C8
0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0
C9	C10	C11	C12	C13	C14	C15	
0,0	0,0	0,0	0,0	0,0	0,0	0,0	

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
0 K	0,0	0,0	0,0	0,0	0,0	0,175	0,708	0,063	0,381	n/a



CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-TOPAZ-COLOURFLOW-RGB3-MEDIUM
[GREEN]

TM30 details


Rf 0,0

Fidelity index Rf

Rg 0,0


Gammut index Rg

		Graphic shifts (%)	
Hue Bin	R _f	Chroma	Hue
1	0	0%	0%
2	0	0%	0%
3	0	0%	0%
4	0	0%	0%
5	0	0%	0%
6	0	0%	0%
7	0	0%	0%
8	0	0%	0%
9	0	0%	0%
10	0	0%	0%
11	0	0%	0%
12	0	0%	0%
13	0	0%	0%
14	0	0%	0%
15	0	0%	0%
16	0	0%	0%




Hue binH

Color vector graphics




Hue bin

Color distortion graphics



Color Evaluation Sample



CLS

CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-TOPAZ-COLOURFLOW-RGB3-MEDIUM [GREEN]

Glare Evaluation According to UGR

p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	7,6	8,1	7,7	8,3	8,5	7,6	8,1	7,7	8,3	8,5
	3H	7,5	8,1	7,9	8,3	8,5	7,5	8,1	7,9	8,3	8,5
	4H	7,5	8,1	7,9	8,3	8,6	7,5	8,1	7,9	8,3	8,6
	6H	7,6	8,1	7,9	8,4	8,7	7,6	8,1	7,9	8,4	8,7
	8H	7,6	8,1	7,9	8,4	8,8	7,6	8,1	7,9	8,4	8,8
	12H	7,6	8,0	7,9	8,4	8,8	7,6	8,0	7,9	8,4	8,8
4H	2H	7,4	8,0	7,8	8,2	8,4	7,4	8,0	7,8	8,2	8,4
	3H	7,5	8,0	7,9	8,3	8,8	7,5	8,0	7,9	8,3	8,8
	4H	7,5	8,0	7,9	8,4	8,9	7,5	8,0	7,9	8,4	8,9
	6H	7,6	8,1	8,1	8,4	8,7	7,6	8,1	8,1	8,4	8,7
	8H	7,6	8,0	8,1	8,3	8,7	7,6	8,0	8,1	8,3	8,7
	12H	7,5	7,9	8,0	8,3	8,7	7,5	7,9	8,0	8,3	8,7
8H	4H	7,5	7,9	8,0	8,3	8,6	7,5	7,9	8,0	8,3	8,6
	6H	7,6	7,9	8,1	8,3	8,8	7,6	7,9	8,1	8,3	8,8
	8H	7,7	7,9	8,2	8,4	9,0	7,7	7,9	8,2	8,4	9,0
	12H	7,6	7,8	8,2	8,3	8,9	7,6	7,8	8,2	8,3	8,9
12H	4H	7,4	7,8	7,9	8,2	8,6	7,4	7,8	7,9	8,2	8,6
	6H	7,6	7,8	8,1	8,3	9,0	7,6	7,8	8,1	8,3	9,0
	8H	7,6	7,8	8,2	8,3	8,9	7,6	7,8	8,2	8,3	8,9

Variation of the observer position for the luminaire distance S

S = 1.0H	3,7 / -3,1	3,7 / -3,1
S = 1.5H	6,1 / -4,2	6,1 / -4,2
S = 2.0H	7,9 / -4,7	7,9 / -4,7
Standard table	n/a	n/a
Correction summand	n/a	n/a

Corrected glare indices referring to 618lm total luminous flux



CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf