

LM-79

Test Report


LM79-TOPAZ-EXPO-2700K-CRI90-NARROW

General Discription


Item number	T-E-XLX-1B-2790-N
Date and time	16-2-2024 10:17:04
CCT (Kelvin)	2723 K
Beam angle	12,7°
Luminous flux	876 lm
Efficiency	80 lm/watt
Weighted energy	10,9 kWh/1000h
Power factor	0,96
CRI (RA)	93,5
Fidelity index Rf	Rf 91,0
Gammut index Rg	Rg 103,4
Peak	14095 cd



Polar diagram



Cartesian diagram



CLS LED BV
info@cls-led.com
www.cls-led.com


2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-TOPAZ-EXPO-2700K-CRI90-NARROW

Beam details	1m	2m	3m	4m	5m
Lux*	14095 lx	3524 lx	1566 lx	881 lx	564 lx



12,7°

*measured at center of beam

Footcandles*	1309,4 fcd	327,4 fcd	145,5 fcd	81,8 fcd	52,4 fcd
Beam width (meter)	0,2 m	0,4 m	0,7 m	0,9 m	1,1 m
Beam width (Feet)	0,7 ft	1,5 ft	2,2 ft	2,9 ft	3,7 ft

Beam intensities																			
1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
14095lx	3524lx	1566lx	881lx	564lx	392lx	288lx	220lx	174lx	141lx	116lx	98lx	83lx	72lx	63lx	55lx	49lx	44lx	39lx	35lx
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
1309,4fcd	327,4fcd	145,5fcd	81,8fcd	52,4fcd	36,4fcd	26,7fcd	20,5fcd	16,2fcd	13,1fcd	10,8fcd	9,1fcd	7,7fcd	6,7fcd	5,8fcd	5,1fcd	4,5fcd	4fcd	3,6fcd	3,3fcd

Intensities in 0° c-plane																			
0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
14,1K	13,9K	13,3K	12,3K	11,0K	9,4K	7,7K	6,0K	4,5K	3,3K	2,4K	1,7K	1,2K	0,8K	0,6K	0,4K	0,3K	0,2K	0,2K	0,1K
100%	99%	95%	88%	78%	67%	54%	42%	32%	23%	17%	12%	8%	6%	4%	3%	2%	2%	1%	1%

Intensities in 90° c-plane																			
0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
14,1K	13,9K	13,3K	12,3K	11,0K	9,4K	7,7K	6,0K	4,5K	3,3K	2,4K	1,7K	1,2K	0,8K	0,6K	0,4K	0,3K	0,2K	0,2K	0,1K
100%	99%	95%	88%	78%	67%	54%	42%	32%	23%	17%	12%	8%	6%	4%	3%	2%	2%	1%	1%

Intensities in 180° c-plane																			
0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
14,1K	13,9K	13,3K	12,3K	11,0K	9,4K	7,7K	6,0K	4,5K	3,3K	2,4K	1,7K	1,2K	0,8K	0,6K	0,4K	0,3K	0,2K	0,2K	0,1K
100%	99%	95%	88%	78%	67%	54%	42%	32%	23%	17%	12%	8%	6%	4%	3%	2%	2%	1%	1%

Intensities in 270° c-plane																			
0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
14,1K	13,9K	13,3K	12,3K	11,0K	9,4K	7,7K	6,0K	4,5K	3,3K	2,4K	1,7K	1,2K	0,8K	0,6K	0,4K	0,3K	0,2K	0,2K	0,1K
100%	99%	95%	88%	78%	67%	54%	42%	32%	23%	17%	12%	8%	6%	4%	3%	2%	2%	1%	1%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
12,7°	22,9°	30,7°	98,9%	97,9%



CLS LED BV
 info@cls-led.com
 www.cls-led.com




2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-TOPAZ-EXPO-2700K-CRI90-NARROW

Color details



CIE 1931

x: 0,460



2723 K


y: 0,413

Spectra

CIE 1931 ZOOM

 $\Delta uv: 0,0009$


CRI: 93,5 (R1-R8)



CRI values, R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8
95,8	94,4	90,3	94,8	94,1	92,3	95,2	91,3
R9	R10	R11	R12	R13	R14	R15	
77,2	84,9	95,0	78,4	95,2	93,3	93,4	


CQS: 90,2



CQS values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8
89,1	96,7	86,5	89,2	89,2	85,3	86,0	92,6
Q9	Q10	Q11	Q12	Q13	Q14	Q15	
94,7	91,6	93,1	94,4	95,2	91,0	90,1	

TM30: 91,0



TM30 values, 16 binned values out of total of 99 values

C1	C2	C3	C4	C5	C6	C7	C8
93,2	94,8	89,0	90,1	91,1	89,6	88,7	91,9
C9	C10	C11	C12	C13	C14	C15	
92,8	93,3	88,1	88,6	92,7	90,4	91,0	

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2723 K	93,5	77,2	91,0	103,4	90,2	0,460	0,413	0,261	0,352	0,0009



CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-TOPAZ-EXPO-2700K-CRI90-NARROW

TM30 details


Rf 91,0

Fidelity index Rf


Rg 103,4

Gamut index Rg


Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	93	-3%	-2%
2	95	-2%	2%
3	89	0%	6%
4	90	2%	6%
5	91	5%	5%
6	90	7%	1%
7	89	5%	-6%
8	92	1%	-5%
9	93	-2%	-4%
10	93	-4%	2%
11	88	-2%	8%
12	89	4%	5%
13	93	5%	0%
14	90	7%	-4%
15	91	3%	-5%
16	88	1%	-9%




Hue binH




Color vector graphics




Hue bin



Color distortion graphics



Color Evaluation Sample



CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-TOPAZ-EXPO-2700K-CRI90-NARROW

Glare Evaluation According to UGR

p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	4,0	4,2	4,0	4,4	4,6	4,0	4,2	4,0	4,4	4,6
	3H	3,9	4,3	4,2	4,5	4,7	3,9	4,3	4,2	4,5	4,7
	4H	3,9	4,4	4,3	4,6	4,8	3,9	4,4	4,3	4,6	4,8
	6H	4,1	4,5	4,4	4,8	5,1	4,1	4,5	4,4	4,8	5,1
	8H	4,1	4,5	4,4	4,8	5,2	4,1	4,5	4,4	4,8	5,2
	12H	4,2	4,5	4,5	4,9	5,3	4,2	4,5	4,5	4,9	5,3
4H	2H	3,7	4,2	4,1	4,4	4,6	3,7	4,2	4,1	4,4	4,6
	3H	3,9	4,3	4,3	4,6	5,0	3,9	4,3	4,3	4,6	5,0
	4H	4,0	4,4	4,4	4,8	5,3	4,0	4,4	4,4	4,8	5,3
	6H	4,2	4,6	4,7	4,9	5,3	4,2	4,6	4,7	4,9	5,3
	8H	4,3	4,6	4,8	5,0	5,3	4,3	4,6	4,8	5,0	5,3
	12H	4,3	4,6	4,8	5,0	5,5	4,3	4,6	4,8	5,0	5,5
8H	4H	4,0	4,4	4,5	4,7	5,1	4,0	4,4	4,5	4,7	5,1
	6H	4,3	4,5	4,8	5,0	5,5	4,3	4,5	4,8	5,0	5,5
	8H	4,5	4,6	5,0	5,2	5,8	4,5	4,6	5,0	5,2	5,8
	12H	4,6	4,8	5,2	5,3	5,9	4,6	4,8	5,2	5,3	5,9
12H	4H	4,0	4,2	4,5	4,6	5,1	4,0	4,2	4,5	4,6	5,1
	6H	4,4	4,5	4,9	5,0	5,6	4,4	4,5	4,9	5,0	5,6
	8H	4,5	4,6	5,1	5,1	5,7	4,5	4,6	5,1	5,1	5,7

Variation of the observer position for the luminaire distance S

S = 1.0H	2,1 / -1,9	2,1 / -1,9
S = 1.5H	4,1 / -2,4	4,1 / -2,4
S = 2.0H	5,7 / -3,2	5,7 / -3,2
Standard table	n/a	n/a
Correction summand	n/a	n/a

Corrected glare indices referring to 876lm total luminous flux



CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf