


LM-79

Test Report


LM79-TOPAZ-EXPO-3000K-CRI98-THRIVE [MEDIUM]

General Discription

Item number	T-E-XLX-1B-3098-M
Date and time	11-9-2024 16:57:27
CCT (Kelvin)	3051 K
Beam angle	24,7°
Luminous flux	815 lm
Efficiency	73 lm/watt
Weighted energy	11,2 kWh/1000h
Power factor	0,88
CRI (RA)	95,3
Fidelity index Rf	Rf 95,9
Gammut index Rg	Rg 100,8
Peak	3919 cd



Polar curve



Linear distribution diagram




CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-TOPAZ-EXPO-3000K-CRI98-THRIVE
[MEDIUM]

Beam details				1m		2m		3m		4m		5m							
Lux*				3892 lx		973 lx		432 lx		243 lx		156 lx							
24,5° 																			
*measured at center of beam																			
Footcandles*				361,6 fcd		90,4 fcd		40,2 fcd		22,6 fcd		14,5 fcd							
Beam width (meter)				0,4 m		0,9 m		1,3 m		1,7 m		2,2 m							
Beam width (Feet)				1,4 ft		2,8 ft		4,3 ft		5,7 ft		7,1 ft							
Beam intensities																			
1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3892lx	973lx	432lx	243lx	156lx	108lx	79lx	61lx	48lx	39lx	32lx	27lx	23lx	20lx	17lx	15lx	13lx	12lx	11lx	10lx
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
361,6fcd	90,4fcd	40,2fcd	22,6fcd	14,5fcd	10fcd	7,4fcd	5,6fcd	4,5fcd	3,6fcd	3fcd	2,5fcd	2,1fcd	1,8fcd	1,6fcd	1,4fcd	1,3fcd	1,1fcd	1fcd	0,9fcd
Intensities in 0° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
3892	3844	3629	3310	2911	2459	1989	1543	1148	817	557	365	232	146	94	63	46	35	28	24
100%	99%	93%	85%	75%	63%	51%	40%	29%	21%	14%	9%	6%	4%	2%	2%	1%	1%	1%	1%
Intensities in 90° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
3892	3786	3584	3274	2889	2455	2006	1576	1190	865	605	406	263	166	106	69	49	37	29	24
100%	97%	92%	84%	74%	63%	52%	40%	31%	22%	16%	10%	7%	4%	3%	2%	1%	1%	1%	1%
Intensities in 180° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
3892	3844	3629	3310	2911	2459	1989	1543	1148	817	557	365	232	146	94	63	46	35	28	24
100%	99%	93%	85%	75%	63%	51%	40%	29%	21%	14%	9%	6%	4%	2%	2%	1%	1%	1%	1%
Intensities in 270° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
3892	3786	3584	3274	2889	2455	2006	1576	1190	865	605	406	263	166	106	69	49	37	29	24
100%	97%	92%	84%	74%	63%	52%	40%	31%	22%	16%	10%	7%	4%	3%	2%	1%	1%	1%	1%
Beam angle 50%				Field angle 10%				Cutoff angle 2,5%				Intensity ratio in 120° cone				Intensity ratio in 90° cone			
24,5°				43,9°				56,2°				99,4%				98,2%			



CLS LED BV
info@cls-led.com
www.cls-led.com




2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-TOPAZ-EXPO-3000K-CRI98-THRIVE
[MEDIUM]

Color details



CIE 1931

x: 0,435



Spectra

CIE 1931 ZOOM


3051 K

y: 0,405

 $\Delta uv: 0,0007$

CRI: 95,3 (R1-R8)


CRI values, R1-R8 are used to calculate final CRI value



R1	R2	R3	R4	R5	R6	R7	R8
94,0	97,4	96,9	92,9	94,1	95,1	97,8	94,3
R9	R10	R11	R12	R13	R14	R15	
89,2	95,4	89,9	93,9	94,6	97,3	95,0	

CQS: 94,8


CQS values



Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8
96,0	96,6	95,5	94,0	94,9	97,0	95,6	94,4
Q9	Q10	Q11	Q12	Q13	Q14	Q15	
94,9	93,8	93,4	92,7	93,6	96,8	96,1	

TM30: 95,9

TM30 values, 16 binned values out of total of 99 values



C1	C2	C3	C4	C5	C6	C7	C8
96,7	95,6	94,2	95,1	96,7	96,5	95,1	95,9
C9	C10	C11	C12	C13	C14	C15	
96,3	95,8	96,6	94,2	95,6	96,8	96,7	

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3051 K	95,3	89,2	95,9	100,8	94,8	0,435	0,405	0,249	0,348	0,0007



CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-TOPAZ-EXPO-3000K-CRI98-THRIVE [MEDIUM]

TM30 details


Rf 95,9

Fidelity index Rf


Rg 100,8

Gamut index Rg


Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	97	1%	0%
2	96	2%	-2%
3	94	0%	-3%
4	95	-2%	-3%
5	97	-3%	0%
6	96	0%	2%
7	95	0%	3%
8	96	2%	1%
9	96	2%	1%
10	96	2%	-1%
11	97	2%	-2%
12	94	1%	-4%
13	96	-1%	-3%
14	97	0%	-1%
15	97	0%	1%
16	96	2%	-2%




Hue binH



Color vector graphics




Hue bin



Color distortion graphics



Color Evaluation Sample



CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

Test Report

LM79-TOPAZ-EXPO-3000K-CRI98-THRIVE
[MEDIUM]

Glare Evaluation According to UGR

p Ceiling	70	70	50	50	30	70	70	50	50	30
p Walls	50	30	50	30	30	50	30	50	30	30
p Floor	20	20	20	20	20	20	20	20	20	20
Room size X Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
Variation of the observer position for the luminaire distance S										
n/a	n/a					n/a				
n/a	n/a					n/a				
n/a	n/a					n/a				
Standard table	n/a					n/a				
Correction summand	n/a					n/a				
Corrected glare indices referring to 815lm total luminous flux										



CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf