


LM-79

Test Report


LM79-TOPAZ-EXPO-3000K-CRI98-THRIVE [WIDE]

General Discription

Item number	T-E-XLX-1B-3098-W
Date and time	11-9-2024 16:54:12
CCT (Kelvin)	3050 K
Beam angle	38,6°
Luminous flux	759 lm
Efficiency	67 lm/watt
Weighted energy	11,2 kWh/1000h
Power factor	0,88
CRI (RA)	95,3
Fidelity index Rf	Rf 96,0
Gammut index Rg	Rg 100,8
Peak	1637 cd



Polar curve



Linear distribution diagram



CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-TOPAZ-EXPO-3000K-CRI98-THRIVE [WIDE]

Beam details		1m	2m	3m	4m	5m
Lux*		1629 lx	407 lx	181 lx	102 lx	65 lx

*measured at center of beam

Footcandles*	151,3 fcd	37,8 fcd	16,8 fcd	9,5 fcd	6,1 fcd
Beam width (meter)	0,7 m	1,4 m	2,1 m	2,8 m	3,5 m
Beam width (Feet)	2,3 ft	4,6 ft	6,9 ft	9,1 ft	11,4 ft

Beam intensities																			
1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
1629lx	407lx	181lx	102lx	65lx	45lx	33lx	25lx	20lx	16lx	13lx	11lx	10lx	8lx	7lx	6lx	6lx	5lx	5lx	4lx
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
151,3fcd	37,8fcd	16,8fcd	9,5fcd	6,1fcd	4,2fcd	3,1fcd	2,4fcd	1,9fcd	1,5fcd	1,3fcd	1,1fcd	0,9fcd	0,8fcd	0,7fcd	0,6fcd	0,5fcd	0,5fcd	0,4fcd	0,4fcd

Intensities in 0° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1629	1626	1596	1549	1486	1407	1309	1191	1053	903	752	608	479	369	279	209	156	117	88	67
100%	100%	98%	95%	91%	86%	80%	73%	65%	55%	46%	37%	29%	23%	17%	13%	10%	7%	5%	4%

Intensities in 90° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1629	1610	1581	1534	1471	1390	1292	1175	1044	905	763	627	503	394	302	229	172	129	97	73
100%	99%	97%	94%	90%	85%	79%	72%	64%	56%	47%	38%	31%	24%	19%	14%	11%	8%	6%	4%

Intensities in 180° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1629	1626	1596	1549	1486	1407	1309	1191	1053	903	752	608	479	369	279	209	156	117	88	67
100%	100%	98%	95%	91%	86%	80%	73%	65%	55%	46%	37%	29%	23%	17%	13%	10%	7%	5%	4%

Intensities in 270° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1629	1610	1581	1534	1471	1390	1292	1175	1044	905	763	627	503	394	302	229	172	129	97	73
100%	99%	97%	94%	90%	85%	79%	72%	64%	56%	47%	38%	31%	24%	19%	14%	11%	8%	6%	4%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
38,4°	64,1°	84°	98,9%	96,7%



CLS LED BV
 info@cls-led.com
 www.cls-led.com




2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-TOPAZ-EXPO-3000K-CRI98-THRIVE [WIDE]

Color details



CIE 1931

x: 0,435



Spectra


CIE 1931 ZOOM

3050 K

y: 0,405

Δuv : 0,0006


CRI: 95,3 (R1-R8)



CRI values, R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8
94,0	97,3	96,9	92,9	94,0	95,0	97,8	94,3
R9	R10	R11	R12	R13	R14	R15	
89,2	95,3	89,8	93,8	94,5	97,3	94,9	


CQS: 94,8



CQS values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8
96,0	96,6	95,5	94,0	94,9	96,9	95,7	94,5
Q9	Q10	Q11	Q12	Q13	Q14	Q15	
95,0	94,0	93,4	92,8	93,7	96,8	96,1	

TM30: 96,0



TM30 values, 16 binned values out of total of 99 values

C1	C2	C3	C4	C5	C6	C7	C8
96,7	95,6	94,3	95,2	96,7	96,5	95,1	95,9
C9	C10	C11	C12	C13	C14	C15	
96,3	95,8	96,6	94,1	95,6	96,8	96,7	

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3050 K	95,3	89,2	96,0	100,8	94,8	0,435	0,405	0,249	0,348	0,0006



CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-TOPAZ-EXPO-3000K-CRI98-THRIVE [WIDE]

TM30 details


Rf 96,0

Fidelity index Rf


Rg 100,8

Gamut index Rg


Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	97	1%	0%
2	96	2%	-2%
3	94	0%	-3%
4	95	-2%	-3%
5	97	-2%	0%
6	97	0%	2%
7	95	0%	3%
8	96	2%	1%
9	96	2%	1%
10	96	2%	-1%
11	97	2%	-2%
12	94	1%	-4%
13	96	-1%	-3%
14	97	0%	-1%
15	97	0%	1%
16	96	2%	-2%




Hue binH



Color vector graphics




Hue bin



Color distortion graphics



Color Evaluation Sample



CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM79-TOPAZ-EXPO-3000K-CRI98-THRIVE [WIDE]

Glare Evaluation According to UGR

p Ceiling	70	70	50	50	30	70	70	50	50	30
p Walls	50	30	50	30	30	50	30	50	30	30
p Floor	20	20	20	20	20	20	20	20	20	20
Room size X Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
Variation of the observer position for the luminaire distance S										
n/a	n/a					n/a				
n/a	n/a					n/a				
n/a	n/a					n/a				
Standard table	n/a					n/a				
Correction summand	n/a					n/a				
Corrected glare indices referring to 759lm total luminous flux										



CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf