

LM-79

Test Report


LM79-TOPAZ-EXPO-3500K-CRI90-SPOT

General Discription


Item number	T-E-XLX-1B-3590-S
Date and time	16-2-2024 11:38:27
CCT (Kelvin)	3454 K
Beam angle	13,7°
Luminous flux	928 lm
Efficiency	87 lm/watt
Weighted energy	10,7 kWh/1000h
Power factor	0,99
CRI (RA)	94,5
Fidelity index Rf	Rf 91,8
Gammut index Rg	Rg 101,4
Peak	12134 cd



Polar diagram



Cartesian diagram




CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-TOPAZ-EXPO-3500K-CRI90-SPOT

Beam details				1m		2m		3m		4m		5m							
Lux*				12134 lx		3034 lx		1348 lx		758 lx		485 lx							
13,7° 																			
*measured at center of beam																			
Footcandles*				1127,3 fcd		281,8 fcd		125,3 fcd		70,5 fcd		45,1 fcd							
Beam width (meter)				0,2 m		0,5 m		0,7 m		1 m		1,2 m							
Beam width (Feet)				0,8 ft		1,6 ft		2,4 ft		3,2 ft		3,9 ft							
Beam intensities																			
1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
12134lx	3034lx	1348lx	758lx	485lx	337lx	248lx	190lx	150lx	121lx	100lx	84lx	72lx	62lx	54lx	47lx	42lx	37lx	34lx	30lx
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
1127,3fcd	281,8fcd	125,3fcd	70,5fcd	45,1fcd	31,3fcd	23fcd	17,6fcd	13,9fcd	11,3fcd	9,3fcd	7,8fcd	6,7fcd	5,8fcd	5fcd	4,4fcd	3,9fcd	3,5fcd	3,1fcd	2,8fcd
Intensities in 0° c-plane																			
0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
12,1K	11,9K	11,4K	10,6K	9,5K	8,4K	7,1K	5,9K	4,8K	3,7K	2,9K	2,2K	1,7K	1,3K	0,9K	0,7K	0,5K	0,4K	0,3K	0,2K
100%	98%	94%	87%	79%	69%	59%	48%	39%	31%	24%	18%	14%	10%	8%	6%	4%	3%	3%	2%
Intensities in 90° c-plane																			
0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
12,1K	11,9K	11,4K	10,6K	9,5K	8,4K	7,1K	5,9K	4,8K	3,7K	2,9K	2,2K	1,7K	1,3K	0,9K	0,7K	0,5K	0,4K	0,3K	0,2K
100%	98%	94%	87%	79%	69%	59%	48%	39%	31%	24%	18%	14%	10%	8%	6%	4%	3%	3%	2%
Intensities in 180° c-plane																			
0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
12,1K	11,9K	11,4K	10,6K	9,5K	8,4K	7,1K	5,9K	4,8K	3,7K	2,9K	2,2K	1,7K	1,3K	0,9K	0,7K	0,5K	0,4K	0,3K	0,2K
100%	98%	94%	87%	79%	69%	59%	48%	39%	31%	24%	18%	14%	10%	8%	6%	4%	3%	3%	2%
Intensities in 270° c-plane																			
0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
12,1K	11,9K	11,4K	10,6K	9,5K	8,4K	7,1K	5,9K	4,8K	3,7K	2,9K	2,2K	1,7K	1,3K	0,9K	0,7K	0,5K	0,4K	0,3K	0,2K
100%	98%	94%	87%	79%	69%	59%	48%	39%	31%	24%	18%	14%	10%	8%	6%	4%	3%	3%	2%
Beam angle 50%				Field angle 10%				Cutoff angle 2,5%				Intensity ratio in 120° cone				Intensity ratio in 90° cone			
13,7°				26,2°				36°				99,3%				98,2%			



CLS LED BV
info@cls-led.com
www.cls-led.com




2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-TOPAZ-EXPO-3500K-CRI90-SPOT

Color details



CIE 1931

x: 0,408



Spectra


CIE 1931 ZOOM

3454 K

y: 0,391

Δuv : -0,0005


CRI: 94,5 (R1-R8)



CRI values, R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8
96,3	95,3	91,6	95,5	94,5	92,1	96,7	93,7
R9	R10	R11	R12	R13	R14	R15	
82,2	86,6	94,6	72,7	96,0	94,4	95,4	


CQS: 92,5



CQS values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8
95,6	98,9	85,0	86,6	92,1	92,8	91,0	95,4
Q9	Q10	Q11	Q12	Q13	Q14	Q15	
96,0	93,1	93,7	95,5	96,9	94,7	94,9	

TM30: 91,8



TM30 values, 16 binned values out of total of 99 values

C1	C2	C3	C4	C5	C6	C7	C8
94,2	95,4	90,9	92,6	92,4	94,3	95,6	96,1
C9	C10	C11	C12	C13	C14	C15	
94,4	87,4	84,1	87,5	94,3	90,5	91,5	

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3454 K	94,5	82,2	91,8	101,4	92,5	0,408	0,391	0,237	0,341	-0,0005



CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-TOPAZ-EXPO-3500K-CRI90-SPOT

TM30 details


Rf 91,8

Fidelity index Rf


Rg 101,4

Gamut index Rg


Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	94	-3%	-1%
2	95	-2%	1%
3	91	-1%	4%
4	93	0%	3%
5	92	0%	3%
6	94	3%	0%
7	96	0%	-1%
8	96	-1%	-1%
9	94	-2%	2%
10	87	-3%	8%
11	84	2%	11%
12	87	5%	6%
13	94	4%	0%
14	90	7%	-3%
15	92	3%	-5%
16	89	2%	-7%




Hue binH



Color vector graphics




Hue bin



Color distortion graphics



Color Evaluation Sample



CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

Glare Evaluation According to UGR

p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	4,6	4,9	4,7	5,1	5,3	4,6	4,9	4,7	5,1	5,3
	3H	4,5	5,0	4,9	5,2	5,4	4,5	5,0	4,9	5,2	5,4
	4H	4,6	5,1	5,0	5,3	5,5	4,6	5,1	5,0	5,3	5,5
	6H	4,7	5,1	5,0	5,4	5,7	4,7	5,1	5,0	5,4	5,7
	8H	4,7	5,1	5,0	5,4	5,8	4,7	5,1	5,0	5,4	5,8
	12H	4,7	5,1	5,0	5,4	5,8	4,7	5,1	5,0	5,4	5,8
4H	2H	4,4	4,9	4,8	5,1	5,3	4,4	4,9	4,8	5,1	5,3
	3H	4,7	5,0	5,0	5,4	5,8	4,7	5,0	5,0	5,4	5,8
	4H	4,7	5,0	5,1	5,4	5,9	4,7	5,0	5,1	5,4	5,9
	6H	4,8	5,2	5,3	5,5	5,8	4,8	5,2	5,3	5,5	5,8
	8H	4,8	5,2	5,3	5,5	5,9	4,8	5,2	5,3	5,5	5,9
	12H	4,8	5,1	5,3	5,5	6,0	4,8	5,1	5,3	5,5	6,0
8H	4H	4,6	5,0	5,1	5,3	5,7	4,6	5,0	5,1	5,3	5,7
	6H	4,8	5,0	5,3	5,5	6,0	4,8	5,0	5,3	5,5	6,0
	8H	4,9	5,1	5,4	5,6	6,2	4,9	5,1	5,4	5,6	6,2
	12H	5,0	5,1	5,6	5,6	6,2	5,0	5,1	5,6	5,6	6,2
12H	4H	4,6	4,9	5,1	5,3	5,7	4,6	4,9	5,1	5,3	5,7
	6H	4,8	5,0	5,4	5,5	6,1	4,8	5,0	5,4	5,5	6,1
	8H	4,9	5,1	5,5	5,6	6,2	4,9	5,1	5,5	5,6	6,2
Variation of the observer position for the luminaire distance S											
S = 1.0H		2,0 / -1,9					2,0 / -1,9				
S = 1.5H		3,9 / -2,8					3,9 / -2,8				
S = 2.0H		5,6 / -3,6					5,6 / -3,6				
Standard table		n/a					n/a				
Correction summand		n/a					n/a				
Corrected glare indices referring to 928lm total luminous flux											