

LM-79

Test Report


LM79-TOPAZ-ZOOM-3500K-CRI90 [WIDE]

General Discription


Item number	T-Z-XLX-1B-3590-Z
Date and time	16-2-2024 11:44:51
CCT (Kelvin)	3461 K
Beam angle	57,6°
Luminous flux	641 lm
Efficiency	60 lm/watt
Weighted energy	10,7 kWh/1000h
Power factor	0,99
CRI (RA)	94,2
Fidelity index Rf	Rf 91,7
Gammut index Rg	Rg 101,1
Peak	851 cd



Polar diagram



Cartesian diagram



CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-TOPAZ-ZOOM-3500K-CRI90 [WIDE]

Beam details	1m	2m	3m	4m	5m
Lux*	851 lx	213 lx	95 lx	53 lx	34 lx

*measured at center of beam

Footcandles*	79,0 fcd	19,8 fcd	8,8 fcd	4,9 fcd	3,2 fcd
Beam width (meter)	1,1 m	2,2 m	3,3 m	4,4 m	5,5 m
Beam width (Feet)	3,6 ft	7,2 ft	10,8 ft	14,4 ft	18 ft

Beam intensities																			
1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
851lx	213lx	95lx	53lx	34lx	24lx	17lx	13lx	11lx	9lx	7lx	6lx	5lx	4lx	4lx	3lx	3lx	3lx	2lx	2lx
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
79fcd	19,8fcd	8,8fcd	4,9fcd	3,2fcd	2,2fcd	1,6fcd	1,2fcd	1fcd	0,8fcd	0,7fcd	0,5fcd	0,5fcd	0,4fcd	0,4fcd	0,3fcd	0,3fcd	0,2fcd	0,2fcd	0,2fcd

Intensities in 0° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
851	850	847	842	834	823	810	793	775	755	733	710	683	629	499	312	145	58	34	27
100%	100%	100%	99%	98%	97%	95%	93%	91%	89%	86%	83%	80%	74%	59%	37%	17%	7%	4%	3%

Intensities in 90° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
851	850	847	842	834	823	810	793	775	755	733	710	683	629	499	312	145	58	34	27
100%	100%	100%	99%	98%	97%	95%	93%	91%	89%	86%	83%	80%	74%	59%	37%	17%	7%	4%	3%

Intensities in 180° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
851	850	847	842	834	823	810	793	775	755	733	710	683	629	499	312	145	58	34	27
100%	100%	100%	99%	98%	97%	95%	93%	91%	89%	86%	83%	80%	74%	59%	37%	17%	7%	4%	3%

Intensities in 270° c-plane																			
0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
851	850	847	842	834	823	810	793	775	755	733	710	683	629	499	312	145	58	34	27
100%	100%	100%	99%	98%	97%	95%	93%	91%	89%	86%	83%	80%	74%	59%	37%	17%	7%	4%	3%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
57,6°	66,2°	79,5°	99,6%	98,6%



CLS LED BV
 info@cls-led.com
 www.cls-led.com




2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-TOPAZ-ZOOM-3500K-CRI90 [WIDE]

Color details



CIE 1931

x: 0,408

3461 K

y: 0,393




Spectra

CIE 1931 ZOOM

Δuv : 0,0002


CRI: 94,2 (R1-R8)



CRI values, R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8
95,9	94,9	91,4	95,4	94,0	91,7	96,8	93,3
R9	R10	R11	R12	R13	R14	R15	
80,7	85,8	94,5	71,9	95,5	94,3	94,8	


CQS: 92,6



CQS values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8
95,4	98,9	85,2	86,7	92,0	92,7	91,2	95,6
Q9	Q10	Q11	Q12	Q13	Q14	Q15	
96,0	93,2	94,0	95,7	97,0	94,4	94,7	

TM30: 91,7



TM30 values, 16 binned values out of total of 99 values

C1	C2	C3	C4	C5	C6	C7	C8
93,9	95,3	91,0	92,7	92,5	94,5	95,6	96,2
C9	C10	C11	C12	C13	C14	C15	
94,2	87,2	84,1	87,6	94,3	90,5	91,4	

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3461 K	94,2	80,7	91,7	101,1	92,6	0,408	0,393	0,237	0,342	0,0002



CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

LM-79

Test Report

LM79-TOPAZ-ZOOM-3500K-CRI90 [WIDE]

TM30 details


Rf 91,7

Fidelity index Rf


Rg 101,1

Gamut index Rg


Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	94	-3%	-1%
2	95	-2%	1%
3	91	-1%	4%
4	93	-1%	3%
5	92	-1%	3%
6	95	3%	0%
7	96	0%	-1%
8	96	-1%	-1%
9	94	-2%	2%
10	87	-3%	8%
11	84	2%	11%
12	88	5%	6%
13	94	4%	0%
14	90	7%	-3%
15	91	3%	-5%
16	89	1%	-7%




Hue binH



Color vector graphics




Hue bin



Color distortion graphics



Color Evaluation Sample



CLS LED BV
info@cls-led.com
www.cls-led.com

2021 CLS-LED BV. All rights reserved. Information subject to change without notice, CLS-LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. No part of this document may be reproduced, in any form or by any means, without permission in writing from CLS-LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website www.cls-led.com/voorwaarden.pdf

Glare Evaluation According to UGR

p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	9,0	9,6	9,1	9,8	10,0	9,0	9,6	9,1	9,8	10,0
	3H	8,7	9,4	9,1	9,6	9,8	8,7	9,4	9,1	9,6	9,8
	4H	8,6	9,3	9,0	9,5	9,8	8,6	9,3	9,0	9,5	9,8
	6H	8,6	9,2	8,9	9,5	9,8	8,6	9,2	8,9	9,5	9,8
	8H	8,6	9,1	8,9	9,5	9,8	8,6	9,1	8,9	9,5	9,8
	12H	8,5	9,1	8,9	9,4	9,8	8,5	9,1	8,9	9,4	9,8
4H	2H	8,6	9,3	9,0	9,5	9,8	8,6	9,3	9,0	9,5	9,8
	3H	8,5	9,1	8,9	9,4	9,8	8,5	9,1	8,9	9,4	9,8
	4H	8,4	8,9	8,8	9,3	9,8	8,4	8,9	8,8	9,3	9,8
	6H	8,3	8,9	8,8	9,2	9,5	8,3	8,9	8,8	9,2	9,5
	8H	8,3	8,8	8,8	9,1	9,5	8,3	8,8	8,8	9,1	9,5
	12H	8,2	8,6	8,7	9,0	9,5	8,2	8,6	8,7	9,0	9,5
8H	4H	8,3	8,8	8,8	9,1	9,5	8,3	8,8	8,8	9,1	9,5
	6H	8,2	8,6	8,7	9,0	9,5	8,2	8,6	8,7	9,0	9,5
	8H	8,2	8,5	8,7	9,0	9,6	8,2	8,5	8,7	9,0	9,6
	12H	8,2	8,4	8,8	8,9	9,5	8,2	8,4	8,8	8,9	9,5
12H	4H	8,2	8,6	8,7	9,0	9,5	8,2	8,6	8,7	9,0	9,5
	6H	8,2	8,5	8,7	9,0	9,6	8,2	8,5	8,7	9,0	9,6
	8H	8,2	8,4	8,8	8,9	9,5	8,2	8,4	8,8	8,9	9,5
Variation of the observer position for the luminaire distance S											
S = 1.0H		6,5 / -9,9					6,5 / -9,9				
S = 1.5H		9,3 / -11,5					9,3 / -11,5				
S = 2.0H		11,2 / -12,0					11,2 / -12,0				
Standard table		n/a					n/a				
Correction summand		n/a					n/a				
Corrected glare indices referring to 641lm total luminous flux											